



ISO/IEC 19752 Yield Test Report

MX910 High Yield Print Cartridge Printer MX910

Declaration of Yield:	Average Cartridge Yield	32,500	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 33,305
Std Dev 897
90% Lower Confidence 32,749

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 8-Mar-2014	<u>stop</u> 14-Mar-2014
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		B11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CRT_MAZDA_021	PTBMFPHV51014	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	32,659	Y
CRT_MAZDA_022	PTBMFPHV51014	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,829	Y
CRT_MAZDA_023	PTBMFPHV51014	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,645	Y
CRT_MERCEDES_016	PTBMFPHV51012	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	34,279	Y
CRT_MERCEDES_017	PTBMFPHV51012	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,501	Y
CRT_MERCEDES_018	PTBMFPHV51012	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	32,474	Y
CRT_MINICOOPER_015	PTBMFPHV51023	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	31,603	Y
CRT_MINICOOPER_016	PTBMFPHV51023	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,432	Y
CRT_MINICOOPER_017	PTBMFPHV51023	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	34,326	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.