



# ISO/IEC 19752 Yield Test Report

## MX911 Ship With Equipment Print Cartridge

Printer MX911

Declaration of Yield:

<b>Average Cartridge Yield</b>	<b>21,000</b>	<b>Standard Pages</b>
<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 22,250  
**Std Dev** 1504  
**90% Lower Confidence** 21,318

**For questions concerning testing contact:**

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date Tested</b>	28-Feb-2014	4-Mar-2014
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		B11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CRT_MUSTANG_09	PTBMFPHV51008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	21,137	Y
CRT_MUSTANG_10	PTBMFPHV51008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	20,738	Y
CRT_MUSTANG_11	PTBMFPHV51008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	21,143	Y
CRT_SORENTO_016	PTBSFPHV51014	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	24,099	Y
CRT_SORENTO_017	PTBSFPHV51014	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	23,153	Y
CRT_SORENTO_018	PTBSFPHV51014	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	21,961	Y
CRT_SUBARU_10	PTBSFPLV01008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,923	Y
CRT_SUBARU_11	PTBSFPLV01008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	24,595	Y
CRT_SUBARU_12	PTBSFPLV01008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	20,498	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.