



ISO/IEC 19752 Yield Test Report

MX911 High Yield Print Cartridge Printer MX911

Declaration of Yield:

Average Cartridge Yield	32,500	Standard Pages
Declared yield in accordance with ISO/IEC 19752		

Average 34,211
Std Dev 1348
90% Lower Confidence 33,376

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 8-Mar-2014	<u>stop</u> 20-Mar-2014
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammmermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		B11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
Cartridge	Printer								
CRT_MUSTANG_13	PTBMFPHV51008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	33,775	Y
CRT_MUSTANG_14	PTBMFPHV51009	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	33,660	Y
CRT_MUSTANG_15	PTBMFPHV51010	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	36,112	Y
CRT_SORENTO_020	PTBSFPHV51014	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	33,579	Y
CRT_SORENTO_021	PTBSFPHV51015	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	32,442	Y
CRT_SORENTO_022	PTBSFPHV51016	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	34,532	Y
CRT_SUBARU_14	PTBSFPLV01008	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	36,657	Y
CRT_SUBARU_15	PTBSFPLV01009	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	33,606	Y
CRT_SUBARU_16	PTBSFPLV01010	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	33,540	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 5.
- *EOL was determined by the printer calling for the cartridge to be replaced.