



# ISO/IEC 19752 Yield Test Report

## MX912 Ship With Equipment Print Cartridge

Printer MX912

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>21,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 22,834  
**Std Dev** 1015  
**90% Lower Confidence** 22,205

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

	<b><u>start</u></b>	<b><u>stop</u></b>
<b>Date Tested</b>	28-Feb-2014	5-Mar-2014
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		B11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CRT_MURANO_016	PTBMFPLV01009	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,218	Y
CRT_MURANO_017	PTBMFPLV01010	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	21,556	Y
CRT_MURANO_018	PTBMFPLV01011	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	25,124	Y
CRT_MAXIMA_09	PTBMFPHV51016	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,423	Y
CRT_MAXIMA_10	PTBMFPHV51017	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,557	Y
CRT_MAXIMA_11	PTBMFPHV51018	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,871	Y
CRT_MONTERO_010	PTBMFPHV51011	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	23,506	Y
CRT_MONTERO_011	PTBMFPHV51012	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,937	Y
CRT_MONTERO_012	PTBMFPHV51013	74 / 23.3	76 / 24.4	70 / 21.1	52	60	48	22,313	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.