



# ISO/IEC 19752 Yield Test Report

## MX912 High Yield Print Cartridge Printer MX912

Declaration of Yield: 

<b>Average Cartridge Yield</b>	<b>32,500</b>	<b>Standard Pages</b>
<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 33,431  
**Std Dev** 906  
**90% Lower Confidence** 32,869

**For questions concerning testing contact:**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<b><u>start</u></b> 8-Mar-2014	<b><u>stop</u></b> 13-Mar-2014
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammmermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		B11
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CRT_MURANO_019	PTBMFPLV01009	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	34,931	Y
CRT_MURANO_020	PTBMFPLV01009	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	32,581	Y
CRT_MURANO_021	PTBMFPLV01009	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	32,520	Y
CRT_MAXIMA_12	PTBMFPHV51016	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,192	Y
CRT_MAXIMA_13	PTBMFPHV51016	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,335	Y
CRT_MAXIMA_14	PTBMFPHV51016	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	34,366	Y
CRT_MONTERO_013	PTBMFPHV51011	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	33,639	Y
CRT_MONTERO_014	PTBMFPHV51011	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	32,254	Y
CRT_MONTERO_015	PTBMFPHV51011	74 / 23.3	76 / 24.4	72 / 22.2	51	59	48	34,058	Y

**Comments and or exceptions:**

- \*The print file was generated with number of copies set equal to 5.
- \*EOL was determined by the printer calling for the cartridge to be replaced.