

MX931 Toner Cartridge

Printer: MX931dse

Declaration of Yield:

Average Cartridge Yield	18,500	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 26,274
Std Dev 1418
90% Lower Confidence 25,395

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 24-Nov-2021 stop 1-Dec-2021

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	No shake
1st shake	No shake
2nd shake	Continuous
Print mode	3
Number of printers tested	Hammermill Tidal MP - 20 lbs. - Letter
Media used	Long Edge Feed (LEF)
Paper feed orientation	Lexmark Printer Software G1
Driver version	Microsoft Server 2012 R Standard
Operating system	Adobe Acrobat DC
Application software	ISO_IEC_19752_Test_Page.pdf
Test page version	

Cartridge testing data:	Cartridge	Printer	Temperature °C			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	JP676K 810012191101900086	PTENMLV000006	22	22	22	45	46	44	24,914	Y
	JP676K 810012191101900087	PTENMLV000006	22	22	22	45	46	44	25,654	Y
	JP676K 810012191101900067	PTENMLV000006	22	22	22	45	46	44	25,071	Y
	JP676K 810012191101900085	PTENMLV000012	22	22	22	45	46	44	25,515	Y
	JP676K 810012191101900088	PTENMLV000012	22	22	22	45	46	44	26,646	Y
	JP676K 810012191101900066	PTENMLV000012	22	22	22	45	46	44	24,972	Y
	JP676K 810012191101900084	PTENMHV000009	22	22	22	45	46	44	27,830	Y
	JP676K 810012191101900068	PTENMHV000009	22	22	22	45	46	44	28,953	Y
	JP676K 810012191101900071	PTENMHV000009	22	22	22	45	46	44	26,909	Y

Comments and or exceptions:

- 1.) The print file was generated with number of copies set equal to 5.