

MX931 Toner Cartridge

Printer: MX931dse

Declaration of Yield:

Average Cartridge Yield	37,000	standard pages
Declared yield value in accordance with ISO/IEC 19752		

Average 39,246
Std Dev 2304
90% Lower Confidence 37,818

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 29-Nov-2021 stop 13-Dec-2021

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake 2nd shake
Print mode	No shake No shake
Number of printers tested	Continuous
Media used	3
Paper feed orientation	Hammermill Tidal MP - 20 lbs. - Letter
Driver version	Long Edge Feed (LEF)
Operating system	Lexmark Printer Software G1
Application software	Microsoft Server 2012 R Standard
Test page version	Adobe Acrobat DC
	ISO_IEC_19752_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature °C			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	JP00CT20369821A1101900064	PTENMLV000006	22	22	22	45	46	44	37,743	Y
	JP00CT20369821A1101900060	PTENMLV000006	22	22	22	45	46	44	42,199	Y
	JP00CT20369821A1101900058	PTENMLV000006	22	22	22	45	46	44	42,658	Y
	JP00CT20369821A1101900063	PTENMLV000012	22	22	22	45	46	44	36,653	Y
	JP00CT20369821A1101900062	PTENMLV000012	22	22	22	45	46	44	39,621	Y
	JP00CT20369821A1101900065	PTENMLV000012	22	22	22	45	46	44	39,870	Y
	JP00CT20369821A1101900061	PTENMHV000009	22	22	22	45	46	44	35,713	Y
	JP00CT20369821A1101900059	PTENMHV000009	22	22	22	45	46	44	39,580	Y
	JP00CT20369821A1101900057	PTENMHV000009	22	22	22	45	46	44	39,176	Y

Comments and or exceptions:

1.) The print file was generated with number of copies set equal to 5.