



# ISO/IEC 19752 Yield Test Report

## SB2338 Starter Print Cartridge

Printer: SB2338

Declaration of Yield	<b>Average Cartridge Yield</b>	<b>1,500</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 1,793  
**Std Dev** 78  
**90% Lower Confidence** 1,745

**For questions concerning testing contact:**  
Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 10-Aug-2017	<u>stop</u> 11-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAS1717024F7	GSMPTB4600027	72	75	70	57	59	53	1,795	Y
CAS1717024F8	GSMPTB4600027	72	75	70	57	59	53	1,804	Y
CAS1717024EF	GSMPTB4600027	72	75	70	57	59	53	1,816	Y
CAS1717024FB	GSMPTB4600007	72	75	70	57	59	53	1,728	Y
CAS1717024DE	GSMPTB4600007	72	75	70	57	59	53	1,909	Y
CAS1717024F9	GSMPTB4600007	72	75	70	57	59	53	1,873	Y
CAS1717024E6	GSMPTB7017220	72	75	70	57	59	53	1,825	Y
CAS17170250E	GSMPTB7017220	72	75	70	57	59	53	1,660	Y
CAS17170250C	GSMPTB7017220	72	75	70	57	59	53	1,724	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.