



# ISO/IEC 19752 Yield Test Report

## SB2338 Print Cartridge

Printer: SB2338

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>3,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 3,368  
**Std Dev** 150  
**90% Lower Confidence** 3,275

**For questions concerning testing contact**  
 Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 15-Aug-2017	<u>stop</u> 18-Aug-2017
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MS520 XL Series
Operating system		Windows 7 Professional
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS17170242B	GSMPTB4600027	72	75	70	56	60	52	3,418	Y
	CAS17170241A	GSMPTB4600027	72	75	70	56	60	52	3,567	Y
	CAS171702424	GSMPTB4600027	72	75	70	56	60	52	3,294	Y
	CAS171702416	GSMPTB4600007	72	75	70	56	60	52	3,179	Y
	CAS1717023F2	GSMPTB4600007	72	75	70	56	60	52	3,314	Y
	CAS17170240B	GSMPTB4600007	72	75	70	56	60	52	3,203	Y
	CAS1717023F3	GSMPTB7017220	72	75	70	56	60	52	3,594	Y
	CAS1717023F4	GSMPTB7017220	72	75	70	56	60	52	3,461	Y
	CAS17170240F	GSMPTB7017220	72	75	70	56	60	52	3,282	Y

### Comments and or exceptions:

- \*The print file was generated with number of copies set equal to 10.
- \*EOL was determined by the printer calling for the cartridge to be replaced.