



ISO/IEC 19752 Yield Test Report

SB2650 Print Cartridge

Printer: SB2650

Declaration of Yield:	Average Cartridge Yield	3,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 3,405
Std Dev 134
90% Lower Confidence 3,322

For questions concerning testing contact
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 14-Aug-2017	<u>stop</u> 16-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
			Avg	Max	Min	Avg	Max	Min		
	SCAS171702415	GSMPTB7018369	73	77	70	56	60	49	3,464	Y
	SCAS171702427	GSMPTB7018369	73	77	70	56	60	49	3,438	Y
	SCAS1717023EA	GSMPTB7018369	73	77	70	56	60	49	3,083	Y
	SCAS171702422	GSMPTB4600160	73	77	70	56	60	49	3,504	Y
	SCAS171702405	GSMPTB4600160	73	77	70	56	60	49	3,339	Y
	SCAS17170241E	GSMPTB4600160	73	77	70	56	60	49	3,545	Y
	SCAS1717023E6	GSMPTB4600134	73	77	70	56	60	49	3,440	Y
	SCAS17170242A	GSMPTB4600134	73	77	70	56	60	49	3,419	Y
	SCAS1717023E9	GSMPTB4600134	73	77	70	56	60	49	3,410	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.