



ISO/IEC 19752 Yield Test Report

SB2650 Starter Print Cartridge

Printer: SB2650

Declaration of Yield	Average Cartridge Yield	5,000	Standard Pages
	Declared yield in accordance with ISO/IEC 19752		

Average 5,364
Std Dev 172
90% Lower Confidence 5,258

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date Tested	<u>start</u> 15-Aug-2017	<u>stop</u> 18-Aug-2017
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	No Shake
	2nd shake	No Shake
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20 lbs. - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark MS520 XL Series	
Operating system	Windows 7 Professional	
Application software	Adobe Acrobat version 9	
Test page version	ISO_IEC_19752_2004_Test_Page.pdf	
Power (off/on) everyday	ON	

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
SCAS171702447	GSMPTB7018369	73	77	70	56	60	49	5,228	Y
SCAS17170242F	GSMPTB7018369	73	77	70	56	60	49	5,411	Y
SCAS171702440	GSMPTB7018369	73	77	70	56	60	49	5,221	Y
SCAS17170243B	GSMPTB4600160	73	77	70	56	60	49	5,250	Y
SCAS171702432	GSMPTB4600160	73	77	70	56	60	49	5,294	Y
SCAS171702451	GSMPTB4600160	73	77	70	56	60	49	5,299	Y
SCAS171702452	GSMPTB4600134	73	77	70	56	60	49	5,696	Y
SCAS17170244A	GSMPTB4600134	73	77	70	56	60	49	5,278	Y
SCAS17170242E	GSMPTB4600134	73	77	70	56	60	49	5,603	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.