



ISO/IEC 19752 Yield Test Report

SB2855 Starter Print Cartridge

Printer: SB2855

| | | | |
|----------------------|--|---------------|-----------------------|
| Declaration of Yield | Average Cartridge Yield | 11,000 | Standard Pages |
| | Declared yield in accordance with ISO/IEC 19752 | | |

Average 12,467
Std Dev 505
90% Lower Confidence 12,154

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

| | | |
|--|--|--------------------------------|
| Date Tested | <u>start</u> 11-Jan-2018 | <u>stop</u> 13-Jan-2018 |
| Number of cartridges in testing | 9 | |
| Qty. of cartridges used in calculation | 9 | |
| Shake Procedure | 1st shake | No Shake |
| | 2nd shake | No Shake |
| Print mode | Continuous | |
| Number of printers tested | 3 | |
| Media used | Hammermill Tidal MP - 20 lbs. - Letter | |
| Paper feed orientation | Short Edge Feed (SEF) | |
| Driver version | 47_G3 | |
| Operating system | Windows 7 Professional | |
| Application software | Adobe Acrobat version 9 | |
| Test page version | ISO_IEC_19752_2004_Test_Page.pdf | |
| Power (off/on) everyday | ON | |

| Cartridge testing data: | | Temperature | | | Humidity | | | Cartridge Yield | Cart used in Calculation |
|-------------------------|---------------|-------------|-----|-----|----------|-----|-----|-----------------|--------------------------|
| Cartridge | Printer | Avg | Max | Min | Avg | Max | Min | | |
| CAS1732011EA | 4064PTBGLA159 | 74 | 76 | 73 | 49 | 50 | 48 | 11,503 | Y |
| CAS17320112B | 4064PTBGLA159 | 74 | 76 | 73 | 50 | 53 | 48 | 12,064 | Y |
| CAS1732010F6 | 4064PTBGLA159 | 73 | 76 | 72 | 50 | 53 | 48 | 12,464 | Y |
| CAS1732011EC | 4064PTBGLA160 | 74 | 76 | 73 | 49 | 50 | 48 | 12,379 | Y |
| CAS1732010CF | 4064PTBGLA160 | 74 | 76 | 73 | 50 | 53 | 48 | 12,420 | Y |
| CAS17320119C | 4064PTBGLA160 | 73 | 76 | 72 | 50 | 53 | 48 | 12,405 | Y |
| CAS173201130 | 4064PTBGLA161 | 74 | 76 | 73 | 49 | 50 | 48 | 12,717 | Y |
| CAS1732011C7 | 4064PTBGLA161 | 74 | 76 | 73 | 50 | 53 | 48 | 13,167 | Y |
| CAS173201100 | 4064PTBGLA161 | 73 | 76 | 72 | 50 | 53 | 48 | 13,084 | Y |

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.