



# ISO/IEC 19752 Yield Test Report

## SB2855 High Yield Print Cartridge

Printer: SB2855

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>15,000</b>	<b>Standard Pages</b>
	<b>Declared yield in accordance with ISO/IEC 19752</b>		

**Average** 17,173  
**Std Dev** 488  
**90% Lower Confidence** 16,870

**For questions concerning testing contact:**

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

<b>Date Tested</b>	<u>start</u> 30-Jan-2018	<u>stop</u> 3-Feb-2018
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake 2nd shake	No Shake No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal MP - 20 lbs. - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		47_G3
Operating system		Windows 7 Professional
Application software		Adobe Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf
Power (off/on) everyday		ON

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg	Max	Min	Avg	Max	Min		
	CAS1732100A7	4064PTBGLA159	74	76	73	50	52	48	16,897	Y
	CAS1732100C1	4064PTBGLA159	74	76	73	50	52	48	16,791	Y
	CAS1732100AB	4064PTBGLA159	74	76	73	50	54	48	16,494	Y
	CAS1732100AA	4064PTBGLA160	74	76	73	50	52	48	17,400	Y
	CAS1732100DB	4064PTBGLA160	74	76	73	50	52	48	16,813	Y
	CAS1732100EF	4064PTBGLA160	74	76	73	50	54	48	17,019	Y
	CAS1732100F5	4064PTBGLA161	74	76	73	50	52	48	17,499	Y
	CAS1732100D8	4064PTBGLA161	74	76	73	50	52	48	17,631	Y
	CAS1732100AD	4064PTBGLA161	74	76	73	50	54	48	18,010	Y

**Comments and or exceptions:**

\*The print file was generated with number of copies set equal to 5.

\*EOL was determined by the printer calling for the cartridge to be replaced.