

LEXMARK TM ISO/IEC 19752 Yield Test Report

MX61X Ship With Equipment Print Cartridge

Printer MX610 / MX611

Declaration of Yield: **Average Cartridge Yield 7,500 Standard Pages**
Declared yield in accordance with ISO/IEC 19752

Average 9,136
Std Dev 379
90% Lower Confidence 8,901

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date Tested	1-May-2012	2-May-2012
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure		
	1st shake	No Shake
	2nd shake	No Shake
Print mode		Continuous
Number of printers tested		3
Media used		Orange Paper - 80gsm - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		Lexmark MX610 Series (B35)
Operating system		Windows XP SP3
Application software		Acrobat version 9
Test page version		ISO_IEC_19752_2004_Test_Page.pdf

Cartridge testing data:	Cartridge	Printer	Temperature			Humidity			Yield	Calculation
			Avg (F/C)	(F/C)	(F/C)	Avg	Max	Min		
(S)CAS120586A0F		4514PTB300207	72	73	71	53	56	49	9,686	Y
(S)CAS120586A04		4514PTB300207	72	73	71	53	56	49	9,004	Y
(S)CAS120586A27		4514PTB300207	72	73	71	53	56	49	8,792	Y
(S)CAS120586A26		4514PTB300205	72	73	71	53	56	49	9,409	Y
(S)CAS1205869F9		4514PTB300205	72	73	71	53	56	49	9,347	Y
(S)CAS120586A2B		4514PTB300205	72	73	71	53	56	49	8,478	Y
(S)CAS120586A23		4514PTB300198	72	73	71	53	56	49	9,437	Y
(S)CAS120586A28		4514PTB300198	72	73	71	53	56	49	9,196	Y
(S)CAS120586A2A		4514PTB300198	72	73	71	53	56	49	8,877	Y

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.