



T632, T634 Extra High Yield Print Cartridge

Printer: T632

Declaration of Yield: Average Cartridge Yield 32000 standard pages. Declared yield value in accordance with ISO/IEC 19752

Average 34063
Std Dev 1250
90% Lower Confidence 33414

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 4-Oct-2004 stop 12-Oct-2004

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 8.4.0.0
Operating system Windows 2000
Application software Adobe Acrobat version 5.0
Test page version Standard\_Testpage\_(PDF\_1.3).pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Contains 15 rows of test data.

Comments and or exceptions: