



T630, T632, T634 High Yield Print Cartridge
Printer: T632

Declaration of Yield: Average Cartridge Yield 21000 standard pages
Declared yield value in accordance with ISO/IEC 19752

Average 23200
Std Dev 1181
90% Lower Confidence 22588

For questions concerning testing contact:
Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 29-Sep-2004 stop 2-Oct-2004

Number of cartridges in testing 12
Qty. of cartridges used in calculation 12
Shake Procedure 1st shake 2nd shake
At toner low
Print mode Continuous
Number of printers tested 4
Media used Boise Cascade X-9 - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version 8.4.0.0
Operating system Windows 2000
Application software Adobe Acrobat version 5.0
Test page version Standard_Testpage_(PDF_1.3).pdf

Table with 13 columns: Cartridge, Printer, Avg °F, Avg °C, Max °F, Max °C, Min °F, Min °C, Humidity Avg, Humidity Max, Humidity Min, Cartridge Yield, Cartridge used in Calculation. Rows include various cartridge models like CAC042260251, CAX042238341, etc.

Comments and or exceptions: