



T630, T632, T634 Print Cartridge

Printer: T632

Declaration of Yield:	Average Cartridge Yield	5000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 6205
Std Dev 728
90% Lower Confidence 5828

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 28-Sep-2004 **stop** 29-Sep-2004

Number of cartridges in testing	12
Qty. of cartridges used in calculation	12
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	4
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	8.4.0.0
Operating system	Windows 2000
Application software	Adobe Acrobat version 5.0
Test page version	Standard_Testpage_(PDF_1.3).pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAX042029097D	9912997	75	24	75	24	74	24	51	52	51	6,093	Yes
CAX042067007D	99129B8	75	24	75	24	74	24	51	52	51	4,866	Yes
CAX041658061D	99104KN	75	24	75	24	74	24	51	52	51	5,467	Yes
CAX041637892D	99129B6	75	24	75	24	74	24	51	52	51	5,696	Yes
CAX041637993D	9912997	75	24	75	24	75	24	51	51	51	7,529	Yes
CAX042029573D	99129B8	75	24	75	24	75	24	51	51	51	6,993	Yes
CAX042066336D	99104KN	75	24	75	24	75	24	51	51	51	5,907	Yes
CAX041658066D	99129B6	75	24	75	24	75	24	51	51	51	5,993	Yes
CAX041658075D	9912997	75	24	75	24	75	24	51	51	51	6,108	Yes
CAX041637908D	99129B8	75	24	75	24	75	24	51	51	51	6,610	Yes
CAX042028927D	99104KN	75	24	75	24	75	24	51	51	51	6,932	Yes
CAX042066327D	99129B6	75	24	75	24	75	24	51	51	51	6,263	Yes

Comments and or exceptions: