



ISO/IEC 19752 Yield Test Report

T640, T642, T644 High Yield Print Cartridge

Printer: T642

Part Number: 64015HA 64017HR 64016HE 64018HL
 64035HA 64037HR 64036HE 64038HL
 64004HA 64004HR 64004HE 64004HL

Declaration of Yield: **Average Cartridge Yield 21000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 25234
Std Dev 1397
90% Lower Confidence 24368

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 14-Apr-2005 stop 17-Apr-2005

Number of cartridges in testing 9
 Qty. of cartridges used in calculation 9
 Shake Procedure 1st shake At toner low
 2nd shake At toner low
 Print mode Continuous
 Number of printers tested 3
 Media used Boise Cascade - 20# - Letter
 Paper feed orientation Short Edge Feed (SEF)
 Driver version T642 version 1
 Operating system Windows 2000
 Application software Acrobat version 6.01
 Test page version Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS050910634	PL3-104-M	73	23	75	24	72	22	53	58	49	24,001	Yes
CAS050910551	PL3-104-M	73	23	75	24	72	22	53	58	49	23,381	Yes
CAS050910550	PL3-104-M	73	23	75	24	72	22	53	58	49	23,821	Yes
CAS050910616	PL3-107-M	73	23	75	24	72	22	53	58	49	24,402	Yes
CAS050910597	PL3-107-M	73	23	75	24	72	22	53	58	49	26,301	Yes
CAS050910573	PL3-107-M	73	23	75	24	72	22	53	58	49	26,761	Yes
CAS050910572	PL3-110-M	73	23	75	24	72	22	53	58	49	25,501	Yes
CAS050910637	PL3-110-M	73	23	75	24	72	22	53	58	49	27,301	Yes
CAS050910604	PL3-110-M	73	23	75	24	72	22	53	58	49	25,641	Yes

Comments and or exceptions: