

T644 Extra High Yield Print Cartridge

See below for additional part numbers

Printer: T644dtn

Declaration of Yield: **Average Cartridge Yield 32000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 33867
Std Dev 1610
90% Lower Confidence 32869

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	start	stop
Date tested	24-Jul-2007	3-Aug-2007
Number of cartridges in testing	9	
Qty. of cartridges used in calculation	9	
Shake Procedure	1st shake	At toner low
	2nd shake	At toner low
Print mode	Continuous	
Number of printers tested	3	
Media used	Hammermill Tidal MP - 20# - Letter	
Paper feed orientation	Short Edge Feed (SEF)	
Driver version	Lexmark T644 PCL version 1.0	
Operating system	Microsoft Windows XP Professional, Ver. 2002, SP2	
Application software	Adobe Reader Version 7.0.9	
Test page version	19752_Test_Chart_Ver.200406.pdf	

Cartridge testing data:	Printer	Temperature			Humidity			Cartridge Yield	Cart used in Calculation
		Avg (F/C)	Max (F/C)	Min (F/C)	Avg	Max	Min		
CAA071161CE0	791BG8H	73/23	74/23	73/23	54	57	51	32,629	Y
CAA071241745	791BG9W	73/23	74/23	73/23	54	57	51	36,940	Y
CAA071290732	791BG91	73/23	74/23	73/23	54	57	51	34,000	Y
CAA07129074C	791BG8H	73/23	74/23	73/23	54	57	49	32,429	Y
CAA071161CD7	791BG9W	73/23	74/23	73/23	54	57	49	34,739	Y
CAA0712416FD	791BG91	73/23	74/23	73/23	54	57	49	35,049	Y
CAA071241725	791BG8H	73/23	74/23	73/23	52	55	49	33,499	Y
CAA071290767	791BG9W	73/23	74/23	73/23	52	55	49	31,549	Y
CAA071161CDD	791BG91	73/23	74/23	73/23	52	55	49	33,971	Y

Comments and or exceptions:

Also Covers:
 64404XA 64416XE 64436XE
 64404XE 64417XR 64437XR
 64404XL 64418XL 64438XL
 64404XR 64435XA