



ISO/IEC 19752 Yield Test Report

T640, T642, T644 Print Cartridge

Printer: T644

Part Number: 64015SA 64017SR 64016SE 64018SL
64035SA 64037SR 64036SE 64038SL

Declaration of **Average Cartridge Yield 6000 standard pages**
Yield: **Declared yield value in accordance with ISO/IEC 19752**

Average 7298
Std Dev 264
90% Lower Confidence 7134

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 31-Mar-2005 stop 1-Apr-2005

Number of cartridges in testing 9
Qty. of cartridges used in calculation 9
Shake Procedure 1st shake At toner low
2nd shake At toner low
Print mode Continuous
Number of printers tested 3
Media used Boise Cascade - 20# - Letter
Paper feed orientation Short Edge Feed (SEF)
Driver version T644 version 1
Operating system Windows 2000
Application software Acrobat version 6.01
Test page version Down load Free__19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS050559091	PL2-1190-H	74	23	75	24	73	23	47	50	45	6,880	Yes
CAS050559104	PL2-1191-H	74	23	75	24	73	23	47	50	45	7,180	Yes
CAS050559131	PL2-1192-H	74	23	75	24	73	23	47	50	45	7,520	Yes
CAS050559037	PL2-1192-H	74	23	75	24	73	23	47	50	45	7,519	Yes
CAS050559084	PL2-1190-H	74	23	75	24	73	23	47	50	45	7,000	Yes
CAS050559139	PL2-1191-H	74	23	75	24	73	23	47	50	45	7,640	Yes
CAS050559021	PL2-1192-H	74	23	75	24	73	23	47	50	45	7,481	Yes
CAS050559056	PL2-1190-H	74	23	75	24	73	23	47	50	45	7,340	Yes
CAS050559089	PL2-1191-H	74	23	75	24	73	23	47	50	45	7,120	Yes

Comments and or exceptions: