



**ISO/IEC 19752 Yield Test
Report**

T650, T652, T654 Print Cartridge, T650 Ship With
Printer: T650

Declaration of Yield:	Average Cartridge Yield	7000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 8975
Std Dev 323
90% Lower Confidence 8775

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested start 7-Aug-2008 stop 8-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS0808019D8	PLT1007	71	22	71	22	70	21	55	57	54	9,339	Yes
CAS0808019EC	PLT1007	70	21	72	22	69	21	55	57	52	8,980	Yes
CAS0808019C2	PLT1007	71	22	72	22	71	21	53	54	52	9,259	Yes
CAS0808019E4	PLT1012	71	22	71	22	70	21	55	56	54	8,887	Yes
CAS0808019B1	PLT1012	71	21	72	22	69	21	55	57	53	8,503	Yes
CAS0808019D6	PLT1012	71	22	72	22	71	21	53	54	52	9,272	Yes
CAS0808019ED	PLT1011	71	22	71	22	70	21	55	56	54	9,253	Yes
CAS0808019E7	PLT1011	70	21	72	22	69	21	55	57	53	8,603	Yes
CAS0808019E9	PLT1011	71	22	72	22	70	21	53	55	52	8,678	Yes

Comments and or exceptions: