



ISO/IEC 19752 Yield Test Report

T650, T652, T654 Print Cartridge
Printer: T652

Declaration of Yield:	Average Cartridge Yield	7000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 8263
Std Dev 135
90% Lower Confidence 8180

For questions concerning testing contact:

Lexmark International Inc.
740 West New Circle Rd.
Lexington, Ky. 40550 USA
Attn: Laser Supplies Product Manager

Date tested **start** 4-Aug-2008 **stop** 5-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	T65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS0808019D5	PLT1051	72	22	73	23	71	22	58	60	57	8,252	Yes
CAS0808019EE	PLT1051	72	22	72	22	71	22	58	59	57	8,119	Yes
CAS080801A15	PLT1051	71	22	72	22	70	21	59	61	58	8,149	Yes
CAS0808019DD	PLT1042	72	22	73	23	71	22	58	59	57	8,230	Yes
CAS0808019E5	PLT1042	72	22	72	22	71	22	58	60	57	8,493	Yes
CAS0808019B3	PLT1042	71	22	73	23	70	21	59	60	58	8,279	Yes
CAS0808019E0	PLT1040	72	22	73	23	71	22	58	59	57	8,422	Yes
CAS080801A13	PLT1040	72	22	72	22	71	22	58	60	57	8,328	Yes
CAS0808019E3	PLT1040	71	22	72	22	70	21	59	60	58	8,098	Yes

Comments and or exceptions: