



ISO/IEC 19752 Yield Test Report

X264 1.5K Ship With Print Cartridge

Printer: X264

Declaration of Yield:	Average Cartridge Yield	1500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 1795
Std Dev 84
90% Lower Confidence 1742

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start stop
 3-Dec-2008 16-Dec-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20# - Letter - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Gold 5
Operating system	Windows XP
Application software	Acrobat version 7.0.9
Test page version	19752_Test_Chart_ver200406.PDF

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN082970150	603057	73	23	74	23	73	23	51	52	49	1,715	Yes
CAN082970155	602025	73	23	74	23	73	23	51	52	49	1,692	Yes
CAN082970153	603052	73	23	74	23	73	23	51	52	49	1,728	Yes
CAN082970152	603057	73	23	75	24	73	23	51	52	50	1,776	Yes
CAN08297014F	602025	73	23	75	24	73	23	51	52	50	1,921	Yes
CAN082970141	603052	73	23	75	24	73	23	51	52	50	1,845	Yes
CAN082970154	603057	73	23	74	23	73	23	51	52	50	1,795	Yes
CAN082970140	602025	73	23	74	23	73	23	51	52	50	1,920	Yes
CAN08297014D	603052	73	23	74	23	73	23	51	52	50	1,761	Yes

Comments and or exceptions: