



ISO/IEC 19752 Yield Test Report

X264, X363, X364 Print Cartridge

Printer: X264

Declaration of Yield:	Average Cartridge Yield	3500	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 4144
Std Dev 109
90% Lower Confidence 4076

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 16-Dec-2008 **stop** 2-Jan-2009

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20# - Letter - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Gold 5
Operating system	Windows XP
Application software	Acrobat version 7.0.9
Test page version	19752_Test_Chart_ver200406.PDF

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN0829500D7	603057	73	23	74	23	73	23	51	53	50	4,228	Yes
CAN0829500EE	602025	73	23	74	23	73	23	51	53	50	4,276	Yes
CAN0829500EA	603052	73	23	74	23	73	23	51	53	50	4,037	Yes
CAN0829500E4	603057	73	23	75	24	73	23	51	52	50	4,075	Yes
CAN0829500D0	602025	73	23	75	24	73	23	51	52	50	4,219	Yes
CAN0829500DB	603052	73	23	75	24	73	23	51	52	50	4,035	Yes
CAN0829500D2	603057	73	23	77	25	72	22	51	53	39	4,243	Yes
CAN0829500D8	602025	73	23	77	25	72	22	51	53	39	4,194	Yes
CAN0829500EC	603052	73	23	77	25	72	22	51	53	39	3,986	Yes

Comments and or exceptions: