



**ISO/IEC 19752 Yield Test Report**

X264, X363, X364 High Yield Print Cartridge

Printer: X264

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>9000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 9913  
**Std Dev** 373  
**90% Lower Confidence** 9682

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 2-Jan-2009      **stop** 23-Jan-2009

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal MP - 20# - Letter - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Gold 5
Operating system	Windows XP
Application software	Acrobat version 7.0.9
Test page version	19752_Test_Chart_ver200406.PDF

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN082980011	603057	74	23	76	24	73	23	48	54	45	9,738	Yes
CAN08298000D	602025	74	23	76	24	73	23	48	54	45	9,816	Yes
CAN08298000F	603052	74	23	76	24	73	23	48	54	45	9,639	Yes
CAN082980023	603057	74	23	75	24	73	23	49	53	46	10,530	Yes
CAN08298001A	602025	74	23	75	24	73	23	49	53	46	9,596	Yes
CAN08297016A	603052	74	23	75	24	73	23	49	53	46	10,276	Yes
CAN082980007	603057	74	23	75	24	74	23	47	51	45	10,296	Yes
CAN082980015	602025	74	23	75	24	74	23	47	51	45	9,424	Yes
CAN082980008	603052	74	23	75	24	74	23	47	51	45	9,904	Yes

**Comments and or exceptions:**