



**ISO/IEC 19752 Yield Test
Report**

X463, X464, X466 Extra High Yield Print Cartridge

Printer: X463

Declaration of Yield:	Average Cartridge Yield	15000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 16288
Std Dev 405
90% Lower Confidence 16036

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 25-Jun-2008 **stop** 2-Jul-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081652310	320065	70	21	71	22	69	20	48	52	45	17,039	Yes
CAS081652311	320032	70	21	71	22	69	20	48	52	45	16,530	Yes
CAS0816522BB	320066	70	21	71	22	69	20	48	52	45	15,840	Yes
CAS08165230F	320065	72	22	74	23	69	20	47	54	40	16,729	Yes
CAS08165230C	320032	72	22	74	23	69	20	47	54	40	15,910	Yes
CAS081652312	320066	72	22	74	23	69	20	47	54	40	16,030	Yes
CAS08165230F	320065	72	22	74	23	70	21	48	54	45	16,100	Yes
CAS0816522B3	320032	72	22	74	23	70	21	48	54	45	16,070	Yes
CAS0816522F0	320066	72	22	74	23	70	21	48	54	45	16,340	Yes

Comments and or exceptions: