



**ISO/IEC 19752 Yield Test Report**

X463, X464, X466 Ship With Print Cartridge

Printer: X463

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>7000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 7232  
**Std Dev** 176  
**90% Lower Confidence** 7124

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 16-Jun-2008      **stop** 18-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS081521416	320065	72	22	74	23	71	22	45	52	39	7,489	Yes
CAS081521411	320032	72	22	74	23	71	22	45	52	39	7,049	Yes
CAS08152141A	320066	72	22	74	23	71	22	45	52	39	7,359	Yes
CAS08152141C	320065	72	22	73	23	70	21	45	54	39	7,310	Yes
CAS081521415	320032	72	22	73	23	70	21	45	54	39	7,229	Yes
CAS08152141D	320066	72	22	73	23	70	21	45	54	39	6,930	Yes
CAS081521414	320065	72	22	73	23	70	21	44	52	38	7,148	Yes
CAS08152141F	320032	72	22	73	23	70	21	44	52	38	7,188	Yes
CAS081521418	320066	72	22	73	23	70	21	44	52	38	7,389	Yes

**Comments and or exceptions:**