



**ISO/IEC 19752 Yield Test
Report**

X463, X464, X466 High Yield Print Cartridge

Printer: X463

Declaration of Yield:	Average Cartridge Yield	9000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 9301
Std Dev 234
90% Lower Confidence 9155

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 10-Jun-2008 **stop** 13-Jun-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Tidal Hammermill - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	Long Bow Lexmark G9
Operating system	Windows XP SP2
Application software	Acrobat version 7.0.0
Test page version	19752_Test_Chart_Ver200406.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS08133305A	320065	72	22	74	23	71	22	50	57	44	9,399	Yes
CAS08133304F	320032	72	22	74	23	71	22	50	57	44	9,209	Yes
CAS081333051	320066	72	22	74	23	71	22	50	57	44	9,209	Yes
CAS08133305F	320065	73	23	75	24	72	22	48	56	43	8,829	Yes
CAS081333061	320032	73	23	75	24	72	22	48	56	43	9,229	Yes
CAS08133304D	320066	73	23	75	24	72	22	48	56	43	9,539	Yes
CAS081333054	320065	71	22	73	23	70	21	52	55	48	9,325	Yes
CAS081333062	320032	71	22	73	23	70	21	52	55	48	9,308	Yes
CAS081333068	320066	71	22	73	23	70	21	52	55	48	9,658	Yes

Comments and or exceptions: