



# ISO/IEC 19752 Yield Test Report

X642e Print Cartridge

Printer: X642e

Part Number(s): X644A11A X644A11P X644A11E X644A11L  
X644A21A X644A21P X644A21E X644A21L

Declaration of Yield: **Average Cartridge Yield 10000 standard pages**  
**Declared yield value in accordance with ISO/IEC 19752**

**Average** 11908  
**Std Dev** 264  
**90% Lower Confidence** 11744

**For questions concerning testing contact:**

Lexmark International Inc.  
740 West New Circle Rd.  
Lexington, Ky. 40550 USA  
Attn: Laser Supplies Product Manager

**Date tested** start 8-Mar-2006 stop 9-Mar-2006

Number of cartridges in testing 9  
Qty. of cartridges used in calculation 9  
Shake Procedure 1st shake At fade  
2nd shake At fade  
Print mode Continuous  
Number of printers tested 3  
Media used Hammermill Copy + Tidal DP - 20# - Letter  
Paper feed orientation Short Edge Feed (SEF)  
Driver version X642E G2  
Operating system Windows XP Professional Version 2002 Service Pack 2  
Application software Adobe Reader version 7.0  
Test page version 19752\_Test\_Chart\_Ver.200406\_.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN06047002A	DVT 2029	73	23	73	23	72	22	48	50	46	12,170	Yes
CAN06047002B	DVT 2028	73	23	73	23	72	22	48	50	46	11,990	Yes
CAN060470013	DVT 2040	73	23	73	23	72	22	48	50	46	11,640	Yes
CAN06047000E	DVT 2029	73	23	73	23	72	22	48	50	46	11,650	Yes
CAN060470011	DVT 2028	73	23	73	23	72	22	48	50	46	12,070	Yes
CAN06047000C	DVT 2040	73	23	73	23	72	22	48	50	46	12,330	Yes
CAN06047000A	DVT 2029	73	23	73	23	72	22	48	50	46	11,860	Yes
CAN060470004	DVT 2028	73	23	73	23	72	22	48	50	46	11,920	Yes
CAN060470028	DVT 2040	73	23	73	23	72	22	48	50	46	11,540	Yes

Comments and or exceptions: