



**ISO/IEC 19752 Yield Test Report**

X651, X652, X654, X656, X658 Print Cartridge

Printer: X651, X652

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>7000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 8492  
**Std Dev** 280  
**90% Lower Confidence** 8319

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 15-Aug-2008      **stop** 18-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS0808019AF	PLT1125	74	23	77	25	69	21	45	53	37	8,260	Yes
CAS0808019C7	PLT1125	71	22	71	22	70	21	49	51	48	8,462	Yes
CAS0808019CF	PLT1125	73	23	77	25	69	21	45	51	37	8,873	Yes
CAS0808019D4	PLT1105	73	23	77	25	69	21	45	52	37	8,842	Yes
CAS0808019C8	PLT1105	73	23	77	25	69	21	45	51	37	8,183	Yes
CAS0808019AE	PLT1105	73	23	76	25	69	21	45	53	36	8,687	Yes
CAS0808019B2	PLT1112	74	23	77	25	69	21	45	53	37	8,373	Yes
CAS0808019B6	PLT1112	73	23	77	25	69	21	45	51	37	8,629	Yes
CAS0808019E1	PLT1112	70	21	71	22	69	21	49	51	47	8,121	Yes

**Comments and or exceptions:**