



ISO/IEC 19752 Yield Test Report

X654, X656, X658 SWE Print Cartridge

Printer: X654, X656

Declaration of Yield:	Average Cartridge Yield	18000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 18953
Std Dev 174
90% Lower Confidence 18845

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested **start** 16-Sep-2008 **stop** 17-Sep-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAN082470233	PLT1100	71	22	72	22	71	21	53	55	52	18,989	Yes
CAN082480010	PLT1100	70	21	72	22	69	21	54	55	52	18,821	Yes
CAN082480004	PLT1100	72	22	72	22	70	21	51	53	51	18,688	Yes
CAN082480006	PLT1068	71	22	72	22	71	22	53	55	52	19,114	Yes
CAN08248000A	PLT1068	70	21	72	22	69	21	54	55	52	18,939	Yes
CAN082470237	PLT1068	71	22	72	22	70	21	51	53	51	18,783	Yes
CAN082470236	PLT1070	71	22	72	22	71	22	53	55	52	19,222	Yes
CAN08247023A	PLT1070	70	21	72	22	69	21	54	55	52	18,911	Yes
CAN082470235	PLT1070	71	22	72	22	69	21	51	53	51	19,111	Yes

Comments and or exceptions: