



**ISO/IEC 19752 Yield Test Report**

X651, X652, X654, X656, X658 High Yield Print Cartridge  
 Printer: X658

Declaration of Yield:	<b>Average Cartridge Yield</b>	<b>25000</b>	<b>standard pages</b>
	<b>Declared yield value in accordance with ISO/IEC 19752</b>		

**Average** 27950  
**Std Dev** 675  
**90% Lower Confidence** 27532

**For questions concerning testing contact:**

Lexmark International Inc.  
 740 West New Circle Rd.  
 Lexington, Ky. 40550 USA  
 Attn: Laser Supplies Product Manager

**Date tested**      **start** 15-Aug-2008      **stop** 23-Aug-2008

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At fade
Print mode	Continuous
Number of printers tested	3
Media used	Hammermill Tidal DP - 20# - Letter
Paper feed orientation	Short Edge Feed (SEF)
Driver version	X65x version 1
Operating system	Windows 2000
Application software	Acrobat version 7.1.0
Test page version	19752 Test Chart.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
CAS08143224C	PLT1112	72	22	73	23	70	21	49	53	47	28,747	Yes
CAS081432264	PLT1112	71	22	72	22	70	21	54	56	52	27,792	Yes
CAS081432272	PLT1112	72	22	73	23	70	21	53	54	52	27,840	Yes
CAS08143223F	PLT1072	71	22	73	23	70	21	52	57	50	28,650	Yes
CAS08143223A	PLT1072	71	22	72	22	70	21	53	56	50	28,007	Yes
CAS08143226C	PLT1072	72	22	73	23	70	21	53	55	50	27,967	Yes
CAS081432251	PLT1118	71	22	73	23	70	21	53	57	50	27,086	Yes
CAS081432259	PLT1118	71	22	72	22	70	21	53	56	50	26,828	Yes
CAS081432271	PLT1118	72	22	73	23	70	21	53	56	50	28,636	Yes

**Comments and or exceptions:**