



ISO/IEC 19752 Yield Test Report

X830e/X832e Print Cartridge

Printer: X832e

Part Numbers: X8302KH

Declaration of Yield:	Average Cartridge Yield	30000	standard pages
	Declared yield value in accordance with ISO/IEC 19752		

Average 33007
Std Dev 833
90% Lower Confidence 32490

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Date tested start 8-Jun-2005 stop 15-Jun-2005

Number of cartridges in testing	9
Qty. of cartridges used in calculation	9
Shake Procedure	1st shake At toner low 2nd shake At toner low
Print mode	Continuous
Number of printers tested	3
Media used	Boise Cascade X-9 - 20# - Letter
Paper feed orientation	Long Edge Feed (LEF)
Driver version	W820 Driver Version 7.4.2
Operating system	Windows XP SP2
Application software	Adobe Acrobat Version 6.0.2
Test page version	IS_19752_Testpage.pdf

Cartridge testing data:		Temperature						Humidity			Cartridge Yield	Cartridge used in Calculation
Cartridge	Printer	Avg °F	Avg °C	Max °F	Max °C	Min °F	Min °C	Avg	Max	Min		
J0-40800-5412K30-CT350006	152970	74	23	75	24	73	23	55	60	53	33,290	Yes
J0-41023-5408K30-CT350006	165579	74	23	75	24	73	23	55	60	53	32,840	Yes
J0-41381-5411K30-CT350006	165601	74	23	75	24	73	23	55	60	53	33,640	Yes
J0-41024-5408K30-CT350006	152970	75	24	75	24	74	23	55	60	52	32,560	Yes
J0-41028-5408K30-CT350006	165579	75	24	75	24	74	23	55	60	52	34,180	Yes
J0-41027-5408K30-CT350006	165601	75	24	75	24	74	23	55	60	52	33,000	Yes
J0-40811-5412K30-CT350006	152970	76	24	77	25	74	23	53	60	47	31,320	Yes
J0-41018-5408K30-CT350006	165579	76	24	77	25	74	23	53	60	47	32,570	Yes
J0-41011-5408K30-CT350006	165601	76	24	77	25	74	23	53	60	47	33,660	Yes

Comments and or exceptions: