

X862 Yield Print Cartridge

Printer: X862

Declaration of Yield: **Average Cartridge Yield 35000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 38656
Std Dev 1180
90% Lower Confidence 37924

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	14-Jan-2009	30-Jan-2009
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		X862 Beta 9
Operating system		Window XP
Application software		Acrobat version 7.0.8
Test page version		19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
JP-CT200677-89J-1001000274	0655306_45	73	74	71	49	50	47	36,820	Y
JP-CT200677-89J-1001000042	0655375_45	73	74	71	49	50	47	38,830	Y
JP-CT200677-89J-1001000091	0655307_45	73	74	71	49	50	47	39,990	Y
JP-CT200677-89J-10010000271	0655306_45	72	73	71	49	51	47	40,310	Y
JP-CT200677-89J-1001000070	0655375_45	72	73	71	49	51	47	38,320	Y
JP-CT200677-89J-1001000092	0655307_45	72	73	71	49	51	47	39,540	Y
JP-CT200677-89J-1001000094	0655306_45	72	73	71	49	51	47	38,360	Y
JP-CT200677-89J-1001000095	0655375_45	72	73	71	49	51	47	38,570	Y
JP-CT200677-89J-1001000067	0655307_45	72	73	71	49	51	47	37,160	Y

Comments and or exceptions:

Also covers the following part number(s):