

X864 Yield Print Cartridge

Printer: X864

Declaration of Yield: **Average Cartridge Yield 35000 standard pages**
Declared yield value in accordance with ISO/IEC 19752

Average 40422
Std Dev 1092
90% Lower Confidence 39745

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	24-Nov-2008	12-Jan-2009
Number of cartridges in testing		9
Qty. of cartridges used in calculation		9
Shake Procedure	1st shake	No shake
	2nd shake	No shake
Print mode		Continuous
Number of printers tested		3
Media used		Hammermill Tidal - 20# - Letter
Paper feed orientation		Long Edge Feed (LEF)
Driver version		X864e Beta 9
Operating system		Window XP
Application software		Acrobat version 7.0.8
Test page version		19752_Test_Chart_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
JP-CT200435-89C-1001000315	0655306_55	73	73	71	44	51	40	39,890	Y
JP-CT200435-89C-1001000371	0655375_55	73	73	71	44	51	40	40,510	Y
JP-CT200435-89C-1001000383	0655307_55	73	73	71	44	51	40	40,390	Y
JP-CT200677-89J-1001000041	0655306_55	73	74	71	49	51	48	38,740	Y
JP-CT200677-89J-1001000049	0655375_55	73	74	71	49	51	48	41,160	Y
JP-CT200677-89J-1001000273	0655307_55	73	74	71	49	51	48	42,250	Y
JP-CT200677-89J-1001000068	0655306_55	73	74	72	49	52	48	39,090	Y
JP-CT200677-89J-1001000050	0655375_55	73	74	72	49	52	48	41,290	Y
JP-CT200677-89J-1001000270	0655307_55	73	74	72	49	52	48	40,480	Y

Comments and or exceptions:

Also covers the following part number(s):