

# LIFE CYCLE ASSESSMENT

## LASER PRINTER MB2236ADW

According to ISO 14040 and ISO 14044



With monochrome output up to 36 pages per minute\* and two-sided printing, the Lexmark MB2236adw offers both impressive performance and affordability. Standard Wi-Fi enhances connectivity and support for mobile users, while both its included fax and scanning are backed up by a 1-GHz processor and 512 MB of memory.



Lexmark's innovative imaging solutions and technologies help customers worldwide print, secure and manage information with ease, efficiency and unmatched value. Lexmark simplifies the complex intersection of digital and printed information.

As part of the commitment to our customers, Lexmark performs Life Cycle Analysis on our products. The results of the LCA analysis continues to assist Lexmark in reducing the environmental impact of the hardware, software and services offered to our customers.

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

This document is the summary of an LCA study aiming to represent the product properties, related assumption, impact categories and potential environmental impact results of Lexmark's MB2236adw printer product. Lexmark generates LCAs for a series of printers and multi-functional devices. The LCAs are critically reviewed by an independent expert. Each LCA is created using the same software model and workflows while changing only printer-specific data points via parameter settings. Each LCA submitted for critical review will then be accompanied by a brief technical summary of the relevant data points, as well as a methodology report.

This LCA study is carried out based on ISO 14040 and ISO 14044, and generally follows the requirements of the Product Category Rules (PCR) Guidance for the product category printers and multi-function printing units, version 2, published by UL Environment (ULE) in April 2018. This LCA study has a few deviations from the PCR, including the following:

- The PCR bases the images per day calculation on the Version 2.0 of the Imaging Equipment ENERGY STAR® Program Requirements. However, using this estimation method results in a calculated printing volume that greatly exceeds actual customer usage. In this study, the images per day calculation has been replaced by actual customer printing data, Average Monthly Print Volumes (AMPV), per product family. The new methodology aligns with realistic customer printing.
- The PCR requires using ReCiPe 2016 or TRACI 2.1 as the impact assessment methodology. This study selects TRACI 2.1 as it is currently the only impact assessment methodology framework that incorporates US average conditions to establish characterization factors (Bare, 2012) (EPA, 2012). For global warming potential, the TRACI characterization factors are not the most current, therefore it is assessed based on the current IPCC characterization factors taken from the 6<sup>th</sup> Assessment Report (IPCC, 2021) for a 100-year timeframe (GWP100) as this is currently the most commonly used metric.
- Sphera updated paper dataset is selected to replace dataset developed based on information from the American Forest and Paper Association (NCASI, 2010).

COMPANY	Lexmark	
PRODUCT SYSTEM	Laser Printer MB2236adw	
REFERENCE STANDARD	<i>ISO 14044: Environmental management— Life cycle assessment— Requirements and guidelines</i> . Geneva: International Organization for Standardization.	
DATE OF ISSUE	11/7/2024	
CONTENTS OF THE REPORT	Product definition Information about basic material and the material's origin Description of the product's manufacture Indication of product processing Information about the in-use conditions Life cycle assessment results Testing results and critical review	
This life cycle assessment was independently reviewed in accordance with ISO 14044 by:		
		Thomas Gloria, Indust. Ecology Consultants

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw  
Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Product Description

---

Product Type	Mono Laser Printer
Printer Model	MB2236adw
Maximum Print Speed	36 pages per minute
Intended use	primarily office
Range of applications	print images or text in mono onto paper or paper-like media
Product Lifetime	5 years
Introduction Date	1/29/2019
Product Specifications	<a href="https://www.lexmark.com/en_us/printer/14205/Lexmark-MB2236adw">https://www.lexmark.com/en_us/printer/14205/Lexmark-MB2236adw</a>
Functional Unit	The functional units has been defined as (1) a 1,000 page simplex job; (2) lifetime page simplex job
Product Characterization	Built on monochrome output up to 36 [34] pages per minute, the Lexmark MB2236adw MFP also includes Wi-Fi, front-panel USB port and convenient e-Task touch screen. The printer product delivered to the customer consists of the printer, a power cord, printed setup instructions, a CD/DVD that includes the User Guide and Printer Drivers and an initial set of product supplies. The printer is delivered in packaging that can be recycled locally and is not needed for product operation. Product supplies include toner cartridges, imaging kits and the fusing mechanism. The power supply is internal to the product and the imaging kit and fusing mechanism are installed at the factory. Only the toner cartridges must be installed by the customer. The printer can be setup by the customer without outside assistance.

# LIFE CYCLE ASSESSMENT



**Lexmark™**

Laser Printer MB2236adw

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Technical Data

Product specifications		Lexmark Black & White All-in-One 2-series (MB2236adw)
<b>Printing</b>		
Display		2-line LCD display
Print Speed: Up to <sup>6</sup>		Black: 36 ppm
Time to First Page: As fast as		Black: 8 seconds
Print Resolution		Black: 1200 IQ (1200 x 600 dpi), 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi
Memory		Standard: 512 MB / Maximum: 512 MB
Hard Disk		Not Available
Recommended Monthly Page Volume <sup>2</sup>		250 - 2500 pages
Maximum Monthly Duty Cycle: Up to <sup>3</sup>		30000 pages per month
<b>Copying</b>		
Copy Speed: Up to <sup>6</sup>		Black: 36 cpm
Time to First Copy: As fast as		Black: 8.5 seconds
<b>Scanning</b>		
Scanner Type / ADF Scan		Flatbed scanner with automatic document feeder / One-sided automatic document feeder
A4/Ltr Simplex Scan Speed: Up to		Black: 23 / 25 sides per minute / Color: 7 / 8 sides per minute
ADF Paper Input Capacity: Up to		50 pages 20 lb or 75 gsm bond
<b>Faxing</b>		
Modem Speed		Max is 33,600 bps, V.34 Half-Duplex Kbps
<b>Supplies<sup>7</sup></b>		
Laser Cartridge Yields (up to) <sup>1</sup>		3,000-page High Yield Cartridge, 6,000-page Extra High Yield Cartridge, 1,200-page Cartridge
Imaging Unit Estimated Yield: Up to		12000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product <sup>1</sup>		700-page Black Return Program Toner Cartridges
<b>Paper Handling</b>		
Included Paper Handling		250-Sheet Input, 150-Sheet Output Bin, Integrated Duplex, Single-Sheet Manual Feed
Paper Input Capacity: Up to		Standard: 251 pages 20 lb or 75 gsm bond / Maximum: 251 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to		Standard: 150 pages 20 lb or 75 gsm bond / Maximum: 150 pages 20 lb or 75 gsm bond
Media Types Supported		Card Stock, Envelopes, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide
Media Sizes Supported		10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6
<b>General Information<sup>4</sup></b>		
Standard Ports		Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n Wireless
Noise Level: Operating		Print: 52 dBA / Copy: 55 dBA / Scan: 52 dBA
Specified Operating Environment		Humidity: 15 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty - See Statement of Limited Warranty		1-Year Advanced Exchange, 3-5 Business Day Ground Shipment
Size (in. - H x W x D) / Weight (lb.)		13.9 x 16.4 x 14.2 in. / 22 lb.

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw  
Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Declaration of Basic Materials

The printer consists of mechanical, electromechanical, and electronic components. Its material composition can be described using the basic material fractions given below. Please note that the category 'Electronics' also includes all wiring.

Material	Mass (kg)
Plastics (recyclable)	5.98
Plastics (non-recyclable)	0.0826
Ferrous Metals	3.76
Aluminum	0.0497
Copper	0
Glass	0.707
Electronics	0.743
Other Materials	0.0508
Total	11.4

Table 1: Basic Material Declaration

## Product Supply Chain

The printer is manufactured and assembled in Southeast China. The cartridges for the North American market are manufactured and assembled in Juarez, Mexico.

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adv

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Life Cycle Assessment Results

The following sections describe the printer's cradle-to-gate resource use and potential environmental impacts over the full printer life cycle. These represent the typical impacts for an average system sold in the North American market. All impacts are presented per functional units.

### Printer Manufacturing Resources Use

Table 2 displays the use of material resources (kg) and of non-renewable as well as renewable primary energy demand necessary for printer manufacturing, but excludes other life cycle stages of the printer (cradle-to-gate). Likewise, material and energy consumption associated with printer packaging, cartridges, and paper is excluded here.

Use of Material Resources [kg]	
Non-Renewable	764
Renewable (excl. water)	1.2E003
Water	3.23E008
Use of Non-Renewable Primary Energy [MJ]	
Crude Oil	323
Hard Coal	689
Lignite	22.2
Natural Gas	604
Uranium	97.5
Use of Renewable Primary Energy [MJ]	
Biomass	2.21E-005
Geothermal	4.19
Solar	139
Wind	68.2
Hydropower	75.7

Table 2: Use of Material and Energy Resources for Printer Manufacturing (Cradle-to-Gate)

### Energy Consumption During Utilization

Based on the ENERGY STAR® Typical Energy Consumption (TEC) test methodology, the printer is expected to have the following power consumption for an assumed average job load.

	Per 1,000 page	Per product lifetime
Energy Consumption During Utilization [kWh]	7.77	140

Table 3: At-wall power consumption during utilization

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adv  
Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Life Cycle Impact Assessment

The following provides an overview of the potential printer life cycle impacts with emissions classified and characterized to standard environmental impact metrics based on TRACI 2.1 method. Global warming potential is evaluated based on IPCC AR6. Ecotoxicity and human toxicity are not included in this study, due to their respective uncertainties.

LCIA results are relative expressions and do not predict impacts on category endpoints, the exceeding of thresholds, safety margins or risks.

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
IPCC AR6 GWP 100, excl biogenic CO <sub>2</sub> [kg CO <sub>2</sub> eq.]	1.52E01	1.21E01	2.75E02	2.18E02
AP [kg SO <sub>2</sub> eq.]	7.45E-02	6.01E-02	1.35E00	1.09E00
EP [kg N eq.]	1.04E-02	2.93E-03	1.88E-01	5.30E-02
ODP [kg CFC 11 eq.]	1.07E-08	1.07E-08	1.93E-07	1.93E-07
RDP [MJ surplus energy]	2.02E01	1.60E01	3.65E02	2.90E02
SFP [kg O <sub>3</sub> eq.]	8.86E-01	6.06E-01	1.60E01	1.10E01

Table 3: Summary of Life Cycle Impact Assessment Results

# LIFE CYCLE ASSESSMENT



**Lexmark**

Laser Printer MB2236adv

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Interpretation of Results

### Dominance Analysis

Due to the 5 year lifetime and the number of pages printed per day based on the actual customer printing information, the use phase dominates the life cycle impacts. The below tables and charts display the results of the dominance analysis for each impact category addressed in Table 3. The first row in each table, labeled Printer, is the printer manufacturing phase which includes raw material extraction and manufacturing.

#### Global Warming Potential

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	6.16E00	6.16E00	1.12E02	1.12E02
Use phase <LC>	8.97E00	5.85E00	1.62E02	1.06E02
EoL phase <LC>	5.54E-02	5.54E-02	1.00E00	1.00E00

Table 4: GWP100 dominance analysis [kg CO2 equiv]




Figure 1: GWP100 dominance analysis of the life cycle stage

Total lifetime distribution: 27.835 kg CO2 equiv

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## *Ozone Depletion Potential*

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	3.54E-09	3.54E-09	6.41E-08	6.41E-08
Use phase <LC>	7.12E-09	7.12E-09	1.29E-07	1.29E-07
EoL phase <LC>	3.96E-16	3.96E-16	7.16E-15	7.16E-15

Table 5: ODP dominance analysis [kg CFC-11 equiv]

## *Acidification Potential*

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	4.23E-02	4.23E-02	7.67E-01	7.67E-01
Use phase <LC>	3.19E-02	1.75E-02	5.77E-01	3.16E-01
EoL phase <LC>	2.69E-04	2.69E-04	4.87E-03	4.87E-03

Table 6: AP dominance analysis [kg SO<sub>2</sub> equiv]

## *Eutrophication Potential*

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	1.70E-03	1.70E-03	3.07E-02	3.07E-02
Use phase <LC>	8.69E-03	1.21E-03	1.57E-01	2.18E-02
EoL phase <LC>	2.32E-05	2.32E-05	4.21E-04	4.21E-04

Table 7: EP dominance analysis [kg N equiv]

## *Resource Depletion Potential (fossil fuel)*

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	7.54E00	7.54E00	1.37E02	1.37E02
Use phase <LC>	1.26E01	8.39E00	2.27E02	1.52E02
EoL phase <LC>	1.03E-01	1.03E-01	1.86E00	1.86E00

Table 8: RDP dominance analysis [MJ surplus energy]

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adv

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## Smog Formation Potential

	per 1000 pages including paper	per 1000 pages excluding paper	per printer lifetime including paper	per printer lifetime excluding paper
Printer	3.24E-01	3.24E-01	5.86E00	5.86E00
Use phase <LC>	5.56E-01	2.76E-01	1.00E01	4.99E00
EoL phase <LC>	6.14E-03	6.14E-03	1.11E-01	1.11E-01

Table 9: SFP dominance analysis [kg O<sub>3</sub> equiv]




Figure 2: Contribution analysis of the use phase (per 1000 pages excluding paper)

## Assumptions and Estimations

Assumptions and estimations are documented in the methodology report, which was provided for critical review purposes alongside this document. The LCA results represent the specific printer model as sold in the North American market.

The model assumes a printer lifetime of five (5) years. The printer is modeled to print an average pages per day

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adv

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

based on actual customer printing information. The printer further possesses an automatic mechanical duplexing feature.

Power consumption figures are based on ENERGY STAR® testing of the printer using the average job load described above. Consumables rate of consumption is based on the market-average yield across all available cartridge capacities. In addition, market-average use of remanufactured cartridges is taken into account, as applicable.

Transportation distances to the end consumer are based on their points of origin and the population-weighted average distance to the 100 most populous cities in the continental US based on 2020 census data. The printer as well as replacement fuser kits and waste toner bottles are manufactured in China and shipped to the point of use from the distribution center near Jeffersonville, IN, while the cartridges and the imaging unit are shipped from Ciudad Juarez, MX to Jeffersonville, IN.

The paper dataset developed by Sphera represents European and used as proxy in lieu of current US data.

The End-of-Life treatment for the printer is based on the assumption that 90 % of the printers are either recycled or remanufactured, while the remainder is disposed of through local waste streams, where the metal fractions are assumed to be recycled and the remainder landfilled. The EoL cartridges are assumed to be split as such: 80% to remanufacturing or recycling, and 20% landfill.

In accordance with the cut-off methodology, materials sent to End-of-Life recycling are considered to cross the system boundary without any further transformation. Only the impacts associated with waste transportation and disposal are included in the results.

## Description of Data and Period Under Consideration

---

All primary data is based on technical documentation and sales data accessed in 2024. All background data is taken from the MLC 2024-10.9.0.20 Databases. No primary data is collected from the Original Equipment Manufacturer's manufacturing plant.

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

---

## Data Quality

---

Manufacturing data of printers and consumables is based on a combination of Bills of Material and teardown analyses and is considered to be of overall high quality with low uncertainty. Distribution from printer manufacturing to the end consumer is representative of logistical data from Lexmark and best estimates of US average shipping distances, and is of moderate quality and high uncertainty.

Printer power consumption represents measured power consumed during printer operation. The electricity consumed is calculated based on TEC specification, and is of high quality and moderate uncertainty. Toner cartridge use is based on expected yields based on the ISO test standards for cartridge use, and is of high quality and low uncertainty. Replacement rate for consumable parts is based on part design specifications, and is of high quality and moderate uncertainty.

The disposition of the printer and consumables at End-of-Life is based on best-available information by the respective experts at Lexmark. This data is of average quality and moderate uncertainty.

---

## Background Data

---

All background datasets relevant to production, power generation, transportation, and material disposal were taken from Sphera's MLC 2024-10.9.0.20 Databases.

The additional use of third-party background data from industry associations (e.g., worldsteel) is documented in the methodology report. They represent the latest LCI data as available in the MLC 2024-10.9.0.20 Databases.

---

## Allocation and Methodological Principles

---

No significant allocations have been considered for the production of the printer. Allocation of production or use impacts across the various functions of a multi-function system is not included (i.e., allocation of production impacts to the provision of scanning services) and the impacts from all life cycle stages are considered within the system boundaries for the printing system.

Treatment of recycled or resold material is not considered in the body of the LCA, in accordance with the cut-off methodology.

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw  
Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

## References and Standards

---

Bare, J. (2012). Tool for the Reduction and Assessment of Chemical and other Environmental Impacts (TRACI) - Software Name and Version Number: TRACI version 2.1 - User's Manual. Washington, D.C.: U.S. EPA.

EPA (2021) ENERGY STAR® Program Requirements for Imaging Equipment – Test Method (Rev. Nov-2021)  
<https://www.energystar.gov/sites/default/files/asset/document/ENERGY%20STAR%20Imaging%20Equipment%20Version%203.2%20Final%20Specification.pdf>

ISO (2006a) ISO 14025: Environmental labels and declarations – Type III environmental declarations – Principles and procedures. International Organization for Standardization. Geneva.

ISO (2006b) ISO 14040: Environmental management - Life cycle assessment – Principles and framework. International Organization for Standardization. Geneva.

ISO (2006c) ISO 14044: Environmental management - Life cycle assessment – Requirements and guidelines. International Organization for Standardization. Geneva.

NCASI (2010) Life Cycle Assessment of North American Printing and Writing Paper Products – Final Report. Prepared for the American Forest and Paper Association (AF&PA) and the Forest Products Association of Canada (FPAC) by the National Council for Air and Stream Improvement, Inc. Research Triangle Park, NC

Sphera. (2025) *LCA for Experts Documentation*. Retrieved from Sphera Solutions, Inc.:  
<https://sphera.com/solutions/product-stewardship/life-cycle-assessment-software-and-data/lca-for-experts/>

ULE (2018) Product Category Rules for preparing an environmental product declaration (EPD) for printers and multi-function printing units (v2.0). UL Environment. Washington, DC. Expired in April, 2023.

## LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw  
Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

---

### Contact Information

---



Lexmark International, Inc.  
740 W. New Circle Road  
Lexington, KY 40550  
Tel: +1-859-232-2000

# LIFE CYCLE ASSESSMENT



Laser Printer MB2236adw

Printers and multi-functional printing units

According to ISO 14040 and ISO 14044

---

## Critical Reviewer:

Thomas P. Gloria, Ph. D.  
Industrial Ecology Consultants  
35 Bracebridge Rd.  
Newton, MA 02459-1728  
direct: 617.553.4929  
email: t.gloria@industrial-ecology.com

Dr. Gloria is a certified Life Cycle Professional (LCACP) through the American Center for Life Cycle Assessment.

# LIFE CYCLE ASSESSMENT



## Letter of Equivalency

---

**LCA Model Evaluated: MB2236adw**

**Equivalent Models: MB2236i**

Life Cycle Assessments (LCA) are in accordance with ISO 14040 and ISO 14044. Life Cycle Assessments provide information on a number of environmental impacts of products over their life cycle. LCAs may be used equivalently for programs with multiple configurations if the differences in configurations are evaluated and determined to be negligible to the global warming impact. Printer configurations with the same parameters for mass, typical electricity consumption (TEC), rated pages per minute are considered equivalent. In many cases, several configurations are identical, but the model names are different among various sales channels. For printer configurations that have slight differences, they are determined to be equivalent only when those differences are considered to have a negligible contribution to the LCA results.

**Accuracy of Results and Comparability:** LCAs regularly rely on estimations of impacts, and the level of accuracy in estimation of effect differs for any particular product line and reported impact. LCAs are not comparative assertions and are either not comparable or have limited comparability when they cover different life cycle stages, are based on different product category rules or are missing relevant environmental impacts. LCAs from different programs may not be comparable.

**Exclusions:** LCAs do not indicate that any environmental or social performance benchmarks are met, and there may be impacts that they do not encompass. LCAs do not typically address the site-specific environmental impacts of raw material extraction, nor are they meant to assess human health toxicity. LCAs can complement but cannot replace tools and certifications that are designed to address these impacts and/or set performance thresholds e.g. Type 1 certifications, health assessments and declarations, environmental impact assessments, etc.

Full details are documented in the LCAs methodology report, which was provided for verification purposes alongside the LCA. Assumptions and estimations generally follow the governing PCR on printing equipment. The LCA results represent the specific printer model as sold in the North American market.