



ISO/IEC 19798 Yield Test Report

C530 Print Cartridge

Printer C530

Part Numbers of Cartridges

Cyan (C) C5200CS, C5202CS
Magenta (M) C5200MS, C5202MS

Yellow (Y) C5200YS, C5202YS
Black (K) C5200KS, C5202KS

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield	1,500 standard pages
Average Continuous Black (K) Cartridge Yield	1,500 standard pages
Declared yield in accordance with ISO/IEC 19798	

Tested Cartridge Summary:

90% Lower Confidence
 Composite Color (CMY) = 1841 pages
 Black = 1672 pages

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

Datum der Tests

20-Jul-2006 23-Jul-2006

Number of cartridges in testing	C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9	K= 9
Type of cartridge	Two piece			
Shake Procedure				
1st shake	At toner low			
2nd shake	At fade			
Print mode	Continuous			
Number of printers tested	3 C530			
Media used	Hammermill Tidal MP - 20# - Letter			
Paper feed orientation	Short Edge Feed (SEF)			
Driver version	Lexmark C534 PS3 1.0			
Operating system	Windows XP			
Application software	Acrobat version 6.01			
Test page version	ISO-IEC 24712 FCD Test Suite - FINAL.pdf			
Power (off/on) everyday	Y			
Pre-generated file used	Y			
Header / Footer used	Y			
Computer	Dell Laptop D610			
Computer RAM and CPU type	504 MB RAM Pentium - 1.86 GHz			
PC / Printer connection	Network			



ISO/IEC 19798 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg	Max	Min	Avg	Max	Min		
K2DT-0182	C	CAN061950194	22 / 72	23 / 73	21 / 71	56	60	54	2045	Y
K2DT-0182	C	CAN0619501B8	22 / 72	23 / 73	21 / 71	56	60	54	1765	Y
K2DT-0182	C	CAN061950191	22 / 72	23 / 73	21 / 70	56	60	54	2120	Y
K2DT-0091	C	CAN0619501AD	22 / 72	23 / 73	22 / 71	56	60	54	2000	Y
K2DT-0091	C	CAN0619501B5	22 / 72	23 / 73	21 / 70	56	60	54	2230	Y
K2DT-0084	C	CAN0619501AC	22 / 72	23 / 73	22 / 71	56	60	54	2145	Y
K2DT-0084	C	CAN06195026F	22 / 72	23 / 73	22 / 71	56	60	54	1945	Y
K2DT-0084	C	CAN0619501B2	22 / 72	23 / 73	21 / 70	56	60	54	1985	Y
K2DT-0091	C	CAN061950195	72 / 22	73 / 23	70 / 21	56	60	54	2085	Y
K2DT-0182	K	CAN0619501A3	22 / 72	23 / 73	22 / 71	56	60	54	1810	Y
K2DT-0182	K	CAN06195022B	72 / 22	73 / 23	71 / 22	56	60	54	1555	Y
K2DT-0182	K	CAN0619501A1	22 / 72	23 / 73	21 / 70	56	60	54	1645	Y
K2DT-0091	K	CAN06195020B	22 / 72	23 / 73	21 / 71	56	60	54	2030	Y
K2DT-0091	K	CAN0615901A4	22 / 72	23 / 73	21 / 70	56	60	54	1945	Y
K2DT-0084	K	CAN0619501A2	22 / 72	23 / 73	22 / 71	56	60	54	1790	Y
K2DT-0084	K	CAN0619501A0	22 / 72	23 / 73	22 / 71	56	60	54	1525	Y
K2DT-0084	K	CAN06195019B	22 / 72	23 / 73	21 / 70	56	60	54	1935	Y
K2DT-0091	K	CAN06195020D	22 / 72	23 / 73	21 / 70	56	60	54	1800	Y
K2DT-0182	M	CAN06195021C	22 / 72	23 / 73	22 / 71	56	60	54	2035	Y
K2DT-0182	M	CAN061950214	22 / 72	23 / 73	22 / 71	56	60	54	1555	Y
K2DT-0182	M	CAN061950216	22 / 72	23 / 73	21 / 70	56	60	54	1910	Y
K2DT-0091	M	CAN061950212	22 / 72	23 / 73	22 / 71	56	60	54	1940	Y
K2DT-0091	M	CAN06195020A	22 / 72	23 / 73	21 / 70	56	60	54	1845	Y
K2DT-0084	M	CAN06195020F	22 / 72	23 / 73	22 / 71	56	60	54	1915	Y
K2DT-0084	M	CAN06195021B	22 / 72	23 / 73	22 / 71	56	60	54	2080	Y
K2DT-0084	M	CAN061950217	22 / 72	23 / 73	21 / 70	56	60	54	1985	Y
K2DT-0091	M	CAN06195026D	22 / 72	23 / 73	21 / 70	56	60	54	2000	Y
K2DT-0182	Y	CAN061950225	22 / 72	23 / 73	21 / 70	56	60	54	1665	Y
K2DT-0182	Y	CAN061950198	72 / 22	73 / 23	70 / 21	56	60	54	1750	Y
K2DT-0091	Y	CAN06195022D	22 / 72	23 / 73	21 / 71	56	60	54	1780	Y
K2DT-0091	Y	CAN061950229	72 / 22	73 / 23	71 / 21	56	60	54	1915	Y
K2DT-0084	Y	CAN061950221	22 / 72	23 / 73	21 / 70	56	60	54	1855	Y
K2DT-0084	Y	CAN06195021E	22 / 72	23 / 73	22 / 71	56	60	54	2170	Y
K2DT-0084	Y	CAN061950226	22 / 72	23 / 73	21 / 70	56	60	54	1810	Y
K2DT-0182	Y	CAN06195022A	22 / 72	23 / 73	21 / 70	56	60	54	1930	Y
K2DT-0091	Y	CAN061950230	22 / 72	23 / 73	21 / 70	56	60	54	1765	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Cyan Cartridge	2036	134	1952
Magenta Cartridge	1918	154	1823
Yellow Cartridge	1849	146	1758
CMY Composite			1841
Black Cartridge	1782	176	1672