

LEXMARK TM ISO/IEC 19752 Yield Test Report

MX711 / MX812 High Yield Print Cartridge Printer MX711 / MX812

Declaration of Yield:

| | | |
|--|---------------|-----------------------|
| Average Cartridge Yield | 25,000 | Standard Pages |
| Declared yield in accordance with ISO/IEC 19752 | | |

Average 30,044
Std Dev 1,881
90% Lower Confidence 28,878

For questions concerning testing contact:
 Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

| | | |
|--|--------------|----------------------------------|
| | start | stop |
| Date Tested | 19-Jul-2012 | 10-Aug-2012 |
| Number of cartridges in testing | | 9 |
| Qty. of cartridges used in calculation | | 9 |
| Shake Procedure | | |
| | 1st shake | No Shake |
| | 2nd shake | No Shake |
| Print mode | | Continuous |
| Number of printers tested | | 3 |
| Media used | | Orange Paper - 80gsm - A4 |
| Paper feed orientation | | Short Edge Feed (SEF) |
| Driver version | | B37 |
| Operating system | | Windows XP SP3 |
| Application software | | Acrobat version 9.1 |
| Test page version | | ISO_IEC_19752_2004_Test_Page.pdf |

| Cartridge testing data: | | Temperature | | | Humidity | | | Cartridge Yield | Cart used in Calculation |
|-------------------------|---------------|-------------|-----------|-----------|----------|-----|-----|-----------------|--------------------------|
| | | Avg (F/C) | Max (F/C) | Min (F/C) | Avg | Max | Min | | |
| Cartridge | Printer | | | | | | | | |
| (S)CAS1219231EC | 746312790009P | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 32,220 | Y |
| (S)CAS1219231EA | 746312790009P | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 32,306 | Y |
| (S)CAS1219231B7 | 746312790009P | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 30,730 | Y |
| (S)CAS1219231E3 | 746312790008C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 30,615 | Y |
| (S)CAS1219231F5 | 746312790008C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 30,726 | Y |
| (S)CAS121923201 | 746312790008C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 30,658 | Y |
| (S)CAS1219231E2 | 746312790009C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 28,294 | Y |
| (S)CAS1219231DA | 746312790009C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 27,397 | Y |
| (S)CAS1219231E5 | 746312790009C | 71 / 21.6 | 75 / 23.8 | 69 / 20.5 | 48 | 57 | 43 | 27,447 | Y |

Comments and or exceptions:

- *The print file was generated with number of copies set equal to 10.
- *EOL was determined by the printer calling for the cartridge to be replaced.