



ISO/IEC 19798 Yield Test Report

X560n Print Cartridge

Printer X560n

Part Numbers of Cartridges

Cyan (C) X560A2CG

Yellow (Y) X560A2YG

Magenta (M) X560A2MG

Black (K) X560A2KG

Lexmark Toner Cartridge Yield Claim:

Average Continuous Composite Color (CMY) Cartridge Yield **4,000** standard pages

Average Continuous Black (K) Cartridge Yield **5,000** standard pages

Declared yield in accordance with ISO/IEC 19798

Tested Cartridge Summary:

90% Lower Confidence

Composite Color (CMY) = 5820 pages

Black = 6696 pages

For questions concerning testing contact:

Lexmark International Inc.

740 West New Circle Rd.

Lexington, Ky. 40550 USA

Attn: Laser Supplies Product Manager

Datum der Tests

3-Oct-2007 12-Oct-2007

Number of cartridges in testing	C= 9	M= 9	Y= 9	K= 9
Qty. of cartridges used in calculation	C= 9	M= 9	Y= 9	K= 9
Type of cartridge	One Piece			
Shake Procedure	No shake			
Print mode	Continuous			
Number of printers tested	3 X560n			
Media used	FX-C2 paper, 70gsm, A4			
Paper feed orientation	Short Edge Feed (SEF)			
Driver version	Lexmark X560 PCL driver (version 0.2.0.3)			
Operating system	Windows XP (Japanese)			
Application software	Adobe Reader 8.1.0			
Test page version	ISO FCD24712, 12/7/2004			
Power (off/on) everyday	Y			
Pre-generated file used	N			
Header / Footer used	N			
Computer	Toshiba Dynabook Satellite J40			
Computer RAM and CPU type	980 MB RAM Pentium ® M - 1.7 GHz			
PC / Printer connection	USB			



ISO/IEC 19798 Yield Test Report

Printer	Color	Cartridge SN	Temperature C / F			Humidity			Cartridge Yield	Cartridge used in Calculation
			Avg	Max	Min	Avg	Max	Min		
23	C	3085	22 / 72	22 / 72	22 / 72	56	56	55	7700	Y
23	C	3093	22 / 72	22 / 72	22 / 72	56	56	55	7679	Y
23	C	3092	22 / 72	22 / 72	22 / 72	55	56	55	7492	Y
29	C	3083	22 / 72	22 / 72	22 / 72	56	56	55	8371	Y
29	C	3097	22 / 72	22 / 72	22 / 72	56	56	55	7992	Y
29	C	3096	22 / 72	22 / 72	22 / 72	55	56	55	7861	Y
36	C	3088	22 / 72	22 / 72	22 / 72	56	56	55	6955	Y
36	C	3091	22 / 72	22 / 72	22 / 72	56	57	55	6402	Y
36	C	3084	22 / 72	22 / 72	22 / 72	56	57	55	6849	Y
23	K	0974	22 / 72	22 / 72	22 / 72	56	56	55	7226	Y
23	K	0946	22 / 72	22 / 72	22 / 72	56	56	55	6677	Y
23	K	0956	22 / 72	22 / 72	22 / 72	55	56	55	7049	Y
29	K	0971	22 / 72	22 / 72	22 / 72	56	56	55	7229	Y
29	K	0966	22 / 72	22 / 72	22 / 72	56	56	55	7117	Y
29	K	0968	22 / 72	22 / 72	22 / 72	55	56	55	6828	Y
36	K	0967	22 / 72	22 / 72	22 / 72	56	56	55	6822	Y
36	K	0963	22 / 72	22 / 72	22 / 72	56	57	55	6239	Y
36	K	0973	22 / 72	22 / 72	22 / 72	56	56	55	6828	Y
23	M	5872	22 / 72	22 / 72	22 / 72	56	56	55	5992	Y
23	M	5862	22 / 72	22 / 72	22 / 72	56	56	55	6012	Y
23	M	5861	22 / 72	22 / 72	22 / 72	56	56	55	6018	Y
29	M	5873	22 / 72	22 / 72	22 / 71	56	56	55	6579	Y
29	M	5870	22 / 72	22 / 72	22 / 72	56	56	55	6208	Y
29	M	5869	22 / 72	22 / 72	22 / 72	56	57	54	5826	Y
36	M	5871	22 / 72	22 / 72	22 / 71	56	56	55	5438	Y
36	M	5867	22 / 72	22 / 72	22 / 71	56	56	55	5235	Y
36	M	5866	22 / 72	22 / 72	22 / 72	56	56	55	5266	Y
23	Y	7790	22 / 72	22 / 72	22 / 72	56	56	55	5554	Y
23	Y	7770	22 / 72	22 / 72	22 / 72	56	57	55	5199	Y
23	Y	7769	22 / 72	22 / 72	22 / 72	56	56	55	5633	Y
29	Y	7789	22 / 72	22 / 72	22 / 72	56	56	55	5763	Y
29	Y	7782	22 / 72	22 / 72	22 / 72	56	56	55	5706	Y
29	Y	7781	22 / 72	22 / 72	22 / 72	56	56	55	5633	Y
36	Y	7787	22 / 72	22 / 72	22 / 72	56	56	55	5054	Y
36	Y	7786	22 / 72	22 / 72	22 / 72	56	56	55	4855	Y
36	Y	7785	22 / 72	22 / 72	22 / 72	56	57	55	4884	Y

	Average	Std Dev. Of Sample	90% Lower Confidence
Cyan Cartridge	7478	625	7090
Magenta Cartridge	5842	450	5562
Yellow Cartridge	5365	366	5138
CMY Composite			5820
Black Cartridge	6891	313	6696