



Lexmark B2236dw

Compact, connected, and affordable, the high-performance Lexmark B2236dw features monochrome output up to 36 [34] pages per minute*, standard Wi-Fi connectivity and two-sided printing.

Part Number

18M0136

Print Technology

Black & White Laser Printer

Workgroup Size

Small Workgroup

Touch Screen Display

No

Display

2-line LCD display

Print Speed (A4, Black)

Up to 34 ppm⁶

Print Speed (A4, Black) Duplex

Up to 17 spm⁶

Time to First Page (Black)

As fast as 7.9 seconds

Duplex (2-sided) Printing

Automatic 2-sided printing

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi

Processor Speed

Dual Core, 1.0 GHz

Memory, Standard

256 MB

Memory, Maximum

256 MB

Hard Disk

Not Available

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 42.3, Fedora 27, 28, 29, Ubuntu 16.04, 18.04 LTS, Red Hat Enterprise Linux WS 6.10, 7.5, 7.6, Debian 9.4, 9.5, 9.6, Debian GNU/Linux 8.11, openSUSE Linux 15

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10, Windows Server 2016, Windows 11

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

250-Sheet Input, 150-Sheet Output Bin, Single-Sheet Manual Feed, Automatic 2-sided printing

Paper Input Capacity, Standard

Up to 251 pages 75 gsm bond

Paper Input Capacity, Maximum

Up to 251 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 150 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 150 pages 75 gsm bond

Paper Weight Range Supported - Standard

Tray (gsm)

60 - 105 gsm

Paper Weight Range Supported - Multipurpose

Feeder (gsm)

60 - 200 gsm

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Ports

Ethernet 10/100BaseTX (RJ-45), USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n Wireless

Direct USB

No

Ethernet Network

Yes

Wireless

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Enhanced IP (Port 9400), FTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area (metric)

5.0 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 5e Emulation, PCL 6 Emulation, Direct Image, PCL 5, PCLm

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

, 3,000-page High Yield Cartridge, 6,000-page Extra High Yield Cartridge, 1,200-page Cartridge

Imaging Unit Estimated Yield

Up to 12000 pages, based on 5 average letter/A4 size pages per print job and ~ 5% coverage for CS/CX96x, CX83x, CX95x, and MX95x printer series, or based on 3 average letter/A4 size pages per print job and ~ 5% coverage for all other printers⁴

Cartridge(s) Shipping with Product

700-page Black Return Program Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

312 x 418 x 443 mm

Packaged Weight, kg

9.62 kg

Size (mm - H x W x D)

215 x 355 x 333 mm

Weight

6.8 kg

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

53 dBA

Duplex Print Noise Level, Operating

50 dBA

Quiet Mode

49 dBA

ENERGY STAR

Yes

Average Power (Sleep Mode)

1.2 watts

Average Power (Ready Mode)

4.0 watts

Average Power (Printing)

460 watts

Average Power while Printing Duplex

320 watts

ENERGY STAR Typical Electricity Consumption (TEC)

0.56 kilowatt-hours per week

Product Warranty

1-Year Onsite Repair

Product Certifications

ENERGY STAR, ICES-003 Class B, US FDA/CDRH, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62311, EN 61000-3, EN 55024, EN 55032, UL), EFTA (CE), KCC, CCC, CECP, CEL, UL-AR, KC mark, ISO 532B, ECMA-370, Customs Union EAC, TER, Wi-Fi CERTIFIED?, China Green Product (CGP)

Maximum Monthly Duty Cycle

Up to 30000 pages per month³

Recommended Monthly Page Volume

250 - 2500 pages²

Specified Operating Environment

Humidity: 15 to 80% Relative Humidity,

Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 metres

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212105

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

P/N	Extended Warranties
2367474	B2236 Upgrade to Onsite Service
2367475	B2236 1-Year Onsite Service
2367476	B2236 3-Years Total (1+2) Onsite Service
2367477	B2236 4-Years Total (1+3) Onsite Service
2367478	B2236 5-Years Total (1+4) Onsite Service
2367479	B2236 1-Year Onsite Service Renewal
2367480	B2236 2-Year Onsite Service Renewal