



Lexmark MX811dxpe

Meet our high performance star. The Lexmark MX811dxpe saves time with blazing-fast processor, print, copy and scan speeds, and gives you the edge with solutions, a staple and hole punch finisher, high input capacity and 2-sided printing.

Part Number

24T8087

Print Technology

Black & White Laser Printer

Function

Colour Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10-inch (25 cm) class colour touch screen

Print Speed (A4, Black)

Do 60 ppm⁶

Hitrost tiskanja (A4, Črno) Duplex

Do 36 spm⁶

Time to First Page (Black) As fast as

Hitrost: 4.4 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 600 x 600 dpi

Copy Speed (A4, Black)

Do 60 cpm⁶

Hitrost kopiranja (A4, Črno) Duplex

Do 36 spm⁶

Time to First Copy (Black) as fast as

Hitrost: 4.2 sekund

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Do 66 / 70 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Do 66 / 70 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Do 132 / 140 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Do 132 / 140 sides per minute

Scan Area, Maximum (mm)

215.9 x 355.6 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CCD

Optical Scanning Resolution

600 X 600 ppi (black), up to 600 X 600 ppi (color)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, XPS, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed

< 3 seconds per page

Processor

Dual Core, 800 MHz

Memory, Standard

1024 MB

Memory, Maximum

3072 MB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.5, 10.6, 10.7, 10.8, 10.9, 10.10)

Citrix MetaFrame

Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5, Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64, Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5

Podprti Linux operacijski sistemi

SUSE Linux Enterprise Server 10, 11, SUSE Linux Enterprise Desktop 10, 11, Red Hat Linux Desktop 6.0, Linpus Linux Desktop 9.6, Debian GNU/Linux 5.0, 6.0, Red Hat Enterprise Linux WS 4.0, 5.0, 6.0, Ubuntu 11.04, 11.10, 12.04, 12.10, openSUSE 11.3, 11.4, 12.1, 12.2, PCLinuxOS 2011, Mint 9, 10, 11, 12, 13, Fedora 14, 15, 16, 17

Podprti Microsoft Windows operacijski sistemi

Windows XP, Windows Server 2003, Windows XP x64, Windows Server 2003 x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server

Podprti UNIX operacijski sistemi

Sun Solaris SPARC 9, 10, HP-UX 11.11, 11.23, 11.31, Sun Solaris x86 10, 11, IBM AIX 5.3, 6.1, 7.1

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Staple Punch Finisher, Integrated Duplex, 2100-Sheet Tray

Paper Input Capacity, Standard

Do 2750 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 2750 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 1050 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 1050 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 176 gsm

Integrated Tray Card Stock Upper limit (grain short)

Cover - 176 gsm (65 lb), Index Bristol - 199 gsm (110 lb), Tag - 203 gsm (125 lb)

ADF

150-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Do 150 strani 20 lbs ali 75 g bond

ADF Paper Output Capacity

Do 150 strani 20 lbs ali 75 g bond

Finishing Option

Standard

Finishing Functions

Offset stacking, Stapling, Hole punching

Number of Paper Inputs, Standard

3

Number of Paper Inputs, Maximum

3

Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

Included

Standard Connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)

Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Internal MarkNet N8350 802.11b/g/n Wireless

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)

Network Management Protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2 mm zgornjih, spodnjih, desni in levih robov (znotraj)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

6,000-page Cartridge, 25,000-page High Yield Cartridge, 45,000-page Extra High Yield Cartridge,

Imaging Unit Estimated Yield

Do 100000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

25,000-page High Yield Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

1567 x 870 x 762 mm

Packaged Weight, kg

129.6 kg

Size (mm - H x W x D)

1374 x 663 x 734 mm

Weight

100.0 kg

Noise level (Idle mode)

31 dBA

Noise Level (Print), Operating

55 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

56 dBA

Noise Level (Scan), Operating

57 dBA

Quiet Mode

51 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.7 watts

Average Power (Sleep Mode)

2.9 watts

Average Power (Ready Mode)

80 watts

Average Power (Printing)

860 watts

Average Power while Printing Duplex

675 watts

Average Power (Copying)

920 watts

Average Power (Scanning)

140 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

4.6 kilowatt-hours per week

Garancija izdelka

1-Year Onsite Service, Next Business Day

Product Certifications

ENERGY STAR, Blue Angel RAL-UZ-171, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECF, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS

Maximum Monthly Duty Cycle

Do 300000 Strani na mesec³

Recommended Monthly Page Volume

5000 - 75000 Strani²

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F), Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 2896 Meters (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)



²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



P/N	Kartuše z barvilom	P/N	Programske rešitve	P/N	Podaljšane garancije
25A0013	Staple Cartridges (3 pack)	24T7351	MX71x, MX81x Forms and Bar Code Card	2355196	MX811 1-Year Onsite Service Renewal
52D0Z00	520Z Black Return Program Imaging Unit	24T7353	MX71x, MX81x Card for PRESCRIBE Emulation	P/N	Deli, ki jih lahko zamenja uporabnik
52D0ZA0	520ZA Black Imaging Unit			40X8421	Return Programme Fuser Maintenance kit, 220-240V Type 01 A4
62D2X00	622X Extra High Yield Return Program Toner Cartridge	P/N	Možnosti povezovanja	40X7706	Roller Maintenance Kit
62D2H00	622H High Yield Return Program Toner Cartridge	27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server	40X8431	ADF Maintenance Kit
62D2000	622 Return Program Toner Cartridge	14F0100	RS-232C Serial Interface Card	40X8426	Fuser Maintenance kit, 220-240V, Type 06, A4
62D0XA0	620XA Extra High Yield Toner Cartridge	SPD0002	Surge Protective Device, 220-240V	P/N	Nadomestni deli
62D2X0E	622XE Extra High Yield Corporate Cartridge	P/N	Podaljšane garancije	40X7600	Multipurpose feeder pick roller
62D2H0E	622HE High Yield Corporate Cartridge	2365447	MX811, XM7163 2 Years renewal OnSite Service, Response Time Next Business Day		
P/N	Možnosti pomnilnika	2365448	MX811, XM7163 3 Years renewal OnSite Service, Response Time Next Business Day		
57X9016	1024MBx32 DDR3-DRAM	2365449	MX811, XM7163 4 Years renewal OnSite Service, Response Time Next Business Day		
57X9012	2048MBx32 DDR3-DRAM	2355192	MX811 2-Years Total (1+1) Onsite Service		
57X9101	256MB Flash Memory Card	2355193	MX811 3-Years Total (1+2) Onsite Service		
57X0070	Removable Hard Disk Enclosure Kit	2355194	MX811 4-Years Total (1+3) Onsite Service		
P/N	Programske rešitve	2355195	MX811 5-Years Total (1+4) Onsite Service		
57X0300	Contact Authentication Device				
57X0301	Contactless Authentication Device				
57X0210	Elatec Reader Authentication Device				
57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264				
24T7352	MX71x, MX81x Card for IPDS				