



Lexmark MX826ade

With output of up to 70 [66] ppm*, long-life imaging components, Ultra High Yield toner capacity, exceptional durability and complete finishing options, the MX826ade is Lexmark's large-workgroup monochrome leader.

Part Number

25B0952

Print Technology

Monochrome Laser

Function

Color Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10-inch (25 cm) class color touch screen

Print Speed (A4, Black)

Up to 66 ppm⁶

Print Speed (A4, Black) Duplex

Up to 40 spm⁶

Time to First Page (Black)

As fast as 4.0 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi

Copy Speed (A4, Colour)

Up to 66 cpm⁶

Copy Speed (A4, Black) Duplex

Up to 42 spm⁶

Time to First Copy (Black)

As fast as 4.0 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 72 / 75 sides per minute

Scan Speed (A4/Ltr, Colour)

Up to 72 / 75 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 144 / 150 sides per minute

Duplex Scan Speed (A4/Ltr, Colour)

Up to 144 / 150 sides per minute

Scan Area, Maximum (mm)

215.9 x 355.6 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CCD

Optical Scanning Resolution

600 X 600 ppi (black), up to 600 X 600 ppi (color)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, XPS, Archival PDF (A-1a, A-1b), Searchable PDF

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

Fax Transmission Speed

< 3 seconds per page

Processor Speed

Quad Core, 1.2 GHz

Memory, Standard

2048 MB

Memory, Maximum

6144 MB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)

Linux Operating Systems Supported

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 12.04 LTS, 14.04 LTS, 15.04, openSUSE Linux 13.2, Ubuntu 16.04 LTS, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

Microsoft Windows Operating Systems Supported

Windows Server 2003, Windows Server 2003 x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

UNIX Operating Systems Supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex, 550-Sheet Tray

Optional Paper Handling

550-Sheet Tray, 4-Bin Mailbox, Offset Stacker, Staple Finisher, Staple Punch Finisher, 2100-Sheet Tray (must remove 1 550-Sheet Tray)

Paper Input Capacity, Standard

Up to 1200 pages 75 gsm bond

Paper Input Capacity, Maximum

Up to 3300 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 550 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 1050 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 176 gsm

Integrated Tray Card Stock Upper limit (grain short)

Cover - 176 gsm (65 lb), Index Bristol - 199 gsm (110 lb), Tag - 203 gsm (125 lb)

ADF

200-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 200 pages 75 gsm bond

ADF Paper Output Capacity

Up to 200 pages 75 gsm bond

Finishing Option

Yes

Number of Paper Inputs, Standard

3

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Dual Web Labels, Envelopes, Integrated Labels, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

Included

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)

Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Marknet N8370 WiFi Option, MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol)

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

7,500-page Cartridge, 15,000-page High Yield Cartridge, 35,000-page Extra High Yield Cartridge, , 55,000-page Ultra High Yield Cartridge

Imaging Unit Estimated Yield

Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

11,000-page Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (mm - H x W x D)

1365 x 770 x 830 mm

Packaged Weight, kg

94.5 kg

Size (mm - H x W x D)

1150.6 x 685.8 x 693.4 mm

Weight

67.0 kg

Noise Level, Idle

14 dBA

Noise Level (Print), Operating

56 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

59 dBA

Noise Level (Scan), Operating

57 dBA

Quiet Mode

50 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

2.9 watts

Average Power (Ready Mode)

50 watts

Average Power (Printing)

850 watts

Average Power while Printing Duplex

640 watts

Average Power (Copying)

900 watts

Average Power (Scanning)

86 watts

ENERGY STAR Typical Electricity Consumption (TEC)

1.21 kilowatt-hours per week

Product Warranty

1-Year Onsite Service, Next Business Day

Product Certifications

ENERGY STAR, Blue Angel RAL-UZ 205, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA/CDRH, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, MET-I, IEC 60825-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CCD-035, CE DoC (EN 62301 Class A, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), CISPR 22 Class A, KCC, CCC, CECF, CEL, A-tick DoC, C-tick CoC, UL-AR, KC mark, UL GS mark, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Bel GISS

Maximum Monthly Duty Cycle

Up to 350000 pages per month³

Recommended Monthly Page Volume

5000 - 100000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 metres

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)


²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Callout	Availability	Description
1	Standard	10-inch (25 cm) Class Touch Screen
10	Optional	4-Bin Mailbox
11	Optional	
12	Optional	
2	Standard	100-Sheet Multipurpose Feeder
3	Standard	
4	Standard	
5	Standard	550-Sheet Tray
6	Standard	Caster Base
7	Optional	Staple Punch Finisher
8	Optional	Staple Finisher
9	Optional	Keyboard

P/N	Toner Cartridges	P/N	User Replaceable Parts
58D0UA0	Lexmark 58D0UA0 Black Ultra High Yield Toner Cartridge	41X0358	ADF Media Pick Roller
58D3000	Lexmark 58D3000 Black Return Programme Toner Cartridge		
58D3H00	Lexmark 58D3H00 Black High Yield Return Programme Toner Cartridge		
58D3X00	Lexmark 58D3X00 Black Extra High Yield Return Programme Toner Cartridge		
58D3U00	Lexmark 58D3U00 Black Ultra High Yield Return Programme Toner Cartridge		
58D0Z00	Lexmark 58D0Z00 Black Return Programme Imaging Unit		
58D0ZA0	Lexmark 58D0ZA0 Black Imaging Unit		
25A0013	Staple Cartridges (3 pack)		

P/N	Paper Handling
25B2900	550-Sheet Tray
25B2950	2,100-Sheet Tray
25B2999	500-Sheet Offset Stacker
50G0849	Staple, Hole Punch Finisher
50G0850	Staple Finisher
50G0852	4-Bin Mailbox

P/N	Memory Options
57X9801	256MB Flash Memory Card
57X0204	4GBx32 DDR3-DRAM

P/N	Application Solutions
40C9201	Card for IPDS
40C9200	Forms and Bar Code Card
40C9202	Card for PRESCRIBE Emulation
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device
57X0210	Elatec Reader Authentication Device
57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264

P/N	Connectivity
27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server
27X6410	Lexmark MarkNet N8372 802.11 a/b/g/n/ac Wireless Print Server
27X6510	MarkNet N8370 802.11 a/b/g/n/ac Wireless Print Server
57X7030	English Keyboard Kit
57X7040	English Keyboard Kit
1021231	Parallel (10') Cable
1021294	USB (2 Meter) Cable
14F0100	RS-232C Serial Interface Card
14F0000	Parallel 1284-B Interface Card

P/N	Extended Warranties
2363846	MX826 2-Years Total (1+1) Onsite Service
2363847	MX826 3-Years Total (1+2) Onsite Service
2363848	MX826 4-Years Total (1+3) Onsite Service
2363849	MX826 5-Years Total (1+4) Onsite Service
2363850	MX826 1-Year Onsite Service Renewal
2363851	MX826 1-Year Post Wty Onsite Repair NBD Warranty
2365476	MX826 6-Years Total (1+5) Onsite Service
2367331	MX826 7-Years Total (1+6) Onsite Service
2365477	MX826 2-Year Onsite Service Renewal
2365478	MX826 3-Year Onsite Service Renewal
2365479	MX826 4-Year Onsite Service Renewal