



Lexmark MX910de

High-volume output, long-life replaceable components, solid security, advanced finishing and SRA3 / 12x18" capability make the Lexmark MX910de the foundation of large-format monochrome multifunction products from Lexmark.

Part Number

26Z0200

Print Technology

Black & White Laser Printer

Function

Colour Scanning, Copying, Faxing, Network Scanning, Printing

Workgroup Size

Departmental Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10-inch (25 cm) class colour touch screen

Print Speed (A4, Black)

Do 45 ppm⁶

Hitrost tiskanja (A4, Črno) Duplex

Do 45 spm⁶

Time to First Page (Black) As fast as

Hitrost: < 5.6 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 600 x 600 dpi

Copy Speed (A4, Black)

Do 45 cpm⁶

Hitrost kopiranja (A4, Črno) Duplex

Do 45 spm⁶

Time to First Copy (Black) as fast as

Hitrost: 5.8 sekund

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Do 80 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Do 80 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Do 140 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Do 140 sides per minute

Scan Area, Maximum (mm)

297 x 432 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CIS / CCD Hybrid

Optical Scanning Resolution

600 X 600 ppi (black), up to 600 X 600 ppi (color)

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, XPS, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed

< 3 seconds per page

Processor

Dual Core, 800 MHz

Memory, Standard

1024 MB

Memory, Maximum

3072 MB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10)

Podprti Linux operacijski sistemi

SUSE Linux Enterprise Server 10, 11, SUSE Linux Enterprise Desktop 10, 11, Red Flag Linux Desktop 6.0, Linpus Linux Desktop 9.6, Debian GNU/Linux 5.0, 6.0, Red Hat Enterprise Linux WS 4.0, 5.0, 6.0, PCLinuxOS 2011, Mint 10, 11, 12, 13, openSUSE 11.4, 12.1, 12.2, Ubuntu 12.04, 12.10, Fedora 17, 18, 19

Podprti Microsoft Windows operacijski sistemi

Windows XP, Windows Server 2003, Windows XP x64, Windows Server 2003 x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server

Podprti UNIX operacijski sistemi

HP-UX 11.11, 11.23, 11.31, Sun Solaris SPARC 9, 10, 11, Sun Solaris x86 10, 11, IBM AIX 5.3, 6.1, 7.1

Included Paper Handling

250-Sheet Output Bin, 150-Sheet Multipurpose Feeder, 2 x 500-Sheet Input

Optional Paper Handling

Staple Punch Finisher, Inline Stapler, 2500-Sheet Tandem Tray, 3000-Sheet Tray, Booklet Finisher, 2 x 500-Sheet Tray

Paper Input Capacity, Standard

Do 1150 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 6650 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 250 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 3500 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 256 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 256 gsm

A3

Yes

ADF

100-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Do 100 strani 20 lbs ali 75 g bond

ADF Paper Output Capacity

Do 100 strani 20 lbs ali 75 g bond

Finishing Option

Yes

Finishing Functions

Offset stacking, Stapling, Hole punching, Booklet fold and saddle stapling

Number of Paper Inputs, Standard

3

Number of Paper Inputs, Maximum

6

Media Types Supported

Card Stock, Envelopes, Labels, Plain Paper, Transparencies, Refer to the Card Stock & Label Guide.

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B4, JIS-B5, Ledger, Legal, Letter, Statement, Universal, Super Tabloid (12 x 18"), Oficio, A6, SRA3

Standard Connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A)

Optional Local Ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Internal MarkNet N8350 802.11b/g/n Wireless

Direct USB

Yes

Ethernet Network

Yes

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2, 3, 3, 3 mm zgornjih, spodnjih, desni in levih robov (znotraj)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, xHTML, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 158 scalable PostScript fonts, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference.

Laser Cartridge Yields (up to)⁵

, 32,500-page High Yield Cartridge

Photoconductor Estimated Yield

Do 125000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

21,000-page Toner Cartridge

Packaged Size (mm - H x W x D)

1194 x 762 x 838 mm

Packaged Weight, kg

112 kg

Size (mm - H x W x D)

909 x 615 x 697 mm

Weight

95 kg

Velikost, povečani predali (mm - V x Š x G)

1307 x 953 x 1246 mm

Noise level (Idle mode)

29 dBA

Noise Level (Print), Operating

52 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

53 dBA

Noise Level (Scan), Operating

57 dBA

ENERGY STAR

No

Average Power (Hibernate Mode)

0.6 watts

Average Power (Sleep Mode)

3.6 watts

Average Power (Ready Mode)

220 watts

Average Power (Printing)

865 watts

Average Power while Printing Duplex

790 watts

Average Power (Copying)

880 watts

Average Power (Scanning)

230 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

1.34 kilowatt-hours per week

Garancija izdelka

1-Year Onsite Service

Product Certifications

ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, cTUV, US FDA/CDRH, cTUVus, IEC 60825-1, CB Report, NCC Mark, FCC, CE (EU) DoC, EFTA (CE), KCC, RCM, CCC, C-tick DoC, EuP, CECF, CEL, ECMA-370, TED, GOST-R, SII, TER, Bel GISS, SABS, TUV-AR, KC mark, BIS, TUV-GS Mark, China Green Product (CGP)

Maximum Monthly Duty Cycle

Do 200000 Strani na mesec³

Recommended Monthly Page Volume

15000 - 50000 Strani²

Specified Operating Environment

Altitude: 0 - 2500 Meters (8,200 Feet), Humidity: 15 to 85% Relative Humidity, Temperature: 10 to 30°C (50 to 86°F)

Country of Origin

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)


²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Standard

Dodatno

P/N	Kartuše z barvilom	P/N	Podaljšane garancije
25A0013	Staple Cartridges (3 pack)	2365492	MX910, MX9145 2 Years renewal OnSite Service, Response Time Next Business Day
64G0H00	MX910, MX911, MX912 High Yield Toner Cartridge (32.5K)	2365493	MX910, MX9145 3 Years renewal OnSite Service, Response Time Next Business Day
54G0P00	Photoconductor Unit (125K)	2365494	MX910, MX9145 4 Years renewal OnSite Service, Response Time Next Business Day
54G0W00	Waste Toner Bottle (90K)	2356829	MX910 2-Years Total (1+1) Onsite Service
		2356830	MX910 3-Years Total (1+2) Onsite Service
		2356831	MX910 4-Years Total (1+3) Onsite Service
		2356832	MX910 5-Years Total (1+4) Onsite Service
		2356833	MX910 1-Year Onsite Service Renewal
P/N	Ravnanje s papirjem	P/N	Nadomestni deli
26Z0087	2500-Sheet Tandem Tray	40X9672	ADF Maintenance Kit
26Z0089	3000-Sheet Tray	40X9704	Image Transfer Kit
26Z0085	2x 500-Sheet Tray	40X9673	Multipurpose Feeder Maintenance Kit
26Z0084	MS911, MX910, MX911 Inline Stapler	40X9669	300K Maintenance Kit
26Z0091	MS911, MX91x Banner Media Tray	40X9046	Fuser
26Z0082	MS911, MX91x Booklet Finisher (4-Hole)	40X9936	Developer unit
26Z0080	MS911, MX91x Staple Punch Finisher (4-Hole)		
P/N	Pohištvo		
26Z0090	Working Shelf		
26Z0094	Cabinet with casters		
P/N	Možnosti pomnilnika		
57X9016	1024MBx32 DDR3-DRAM		
57X9012	2048MBx32 DDR3-DRAM		
57X9101	256MB Flash Memory Card		
57X0070	Removable Hard Disk Enclosure Kit		
P/N	Programske rešitve		
57X0300	Contact Authentication Device		
57X0301	Contactless Authentication Device		
57X0210	Elatec Reader Authentication Device		
57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264		
26Z0196	MX910, MX911, MX912 Card for IPDS		
26Z0195	MX91x Forms and Bar Code Card		
26Z0197	MX910, MX911, MX912 Card for PRESCRIBE Emulation		
P/N	Možnosti povezovanja		
27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server		
14F0100	RS-232C Serial Interface Card		
57X7000	English Keyboard Kit		
57X7002	Italian Keyboard Kit		
SPD0002	Surge Protective Device, 220-240V		
P/N	Podaljšane garancije		
2365491	MX910, MX9145 6 Years Total (1+5) Onsite Repair Next Business Day		