



Lexmark CX924dxe

Tray input of 3500 sheets enhances the multi-format 65-ppm MFP that already offers SRA3/12x18 output, copying, scanning, faxing and optional finishing.

Part Number

32C0235

Print Technology

Colour Laser

Function

Colour Copying, Colour Faxing, Colour Printing, Colour Scanning, Colour Network Scanning

Workgroup Size

Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10-inch (25 cm) class colour touch screen

Print Speed (A4, Black)

Up to 65 ppm⁶

Print Speed (A4, Colour)

Up to 65 ppm⁶

Print Speed (A4, Black) Duplex

Up to 65 spm⁶

Time to First Page (Black)

As fast as 5.0 seconds

Time to First Page (Colour)

As fast as 5.9 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi)

Copy Speed (A4, Black)

Up to 65 cpm⁶

Copy Speed (A4, Colour)

Up to 65 cpm⁶

Time to First Copy (Black)

As fast as 4.8 seconds

Time to First Copy (Colour)

As fast as 5.5 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 80 / 80 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Up to 80 / 80 sides per minute

A4/Ltr Duplex Scan Speed (Black)

Up to 160 / 160 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Up to 160 / 160 sides per minute

Scan Area, Maximum (mm)

297 x 432 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

CCD

Optical Scanning Resolution

600 X 600 dpi

Scan File Formats (Send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Highly compressed PDF (1GB RAM and hard disk required), Searchable PDF

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

Modem Speed

ITU T.30, V.34 Half-Duplex, 33.6 Kbps

Fax Transmission Speed

< 3 seconds per page

Processor Speed

Quad Core 1.2 GHz

Memory, Standard

2048 MB

Memory, Maximum

4096 MB

Hard Disk

Included in configuration

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11)

Citrix MetaFrame

Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Debian GNU/Linux 7.0, 8.0, Fedora 21, 22, Linpus Linux Lite Desktop 2.1, Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS, Linux Mint 2 Debian, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 4, 5, 6, 7, SUSE Linux Enterprise Desktop 10, 11, 12, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 12.04 LTS, 14.04 LTS, 15.04, openSUSE 13.1, 13.2, openSUSE Tumbleweed

Microsoft Windows Operating Systems Supported

Windows XP, Windows XP x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server on SuSE Linux Enterprise Server 10 SP4 (x86 and x64), Novell Open Enterprise Server on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server on SuSE Linux Enterprise Server 12 SP1 (x86 and x64)

UNIX Operating Systems Supported

Sun Solaris x86 10, 11, IBM AIX 5.3, 6.1, 7.1, Sun Solaris SPARC 10, 11

Included Paper Handling

Integrated Duplex, 250-Sheet Output Bin, 150-Sheet Multipurpose Feeder, 2 x 500-Sheet Input, 2500-Sheet Tandem Tray

Optional Paper Handling

Staple Finisher, Staple Punch Finisher, 3000-Sheet Tray, Booklet Finisher

Paper Input Capacity, Standard

Up to 3650 pages 75 gsm bond

Paper Input Capacity, Maximum

Up to 6650 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 250 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 3500 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 300 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 300 gsm

A3

Yes

ADF

100-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 100 pages 75 gsm bond

ADF Paper Output Capacity

Up to 100 pages 75 gsm bond

Finishing Option

Yes

Finishing Functions

Offset stacking, Stapling, Hole punching, Booklet fold and saddle stapling

Number of Paper Inputs, Standard

4

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Envelopes, Labels, Plain Paper, Banner Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A3, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Super Tabloid (304.8 x 483 mm), Oficio, A6, SRA3

Caster Base

Optional

Standard Connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Two Rear USB 2.0 Specification Hi-Speed Certified ports (Type A), Two Front USB 2.0 Specification Hi-Speed Certified port (Type A)

Optional Local Ports

External RS-232C serial, Internal 1284-B Bidirectional Parallel

Optional Network Ports

Internal MarkNet N8360 802.11b/g/n Wireless, NFC, MarkNet N8230 Fiber Ethernet Print Server

Direct USB

Yes

Ethernet Network

Yes

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2, 3, 3, 3 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 165 scalable PostScript fonts, 15 PPDS bitmap fonts

Laser Cartridge Yields (up to)⁵

, 18,500-page Black Cartridge, 11,500-page Colour (CMY) Cartridges, 34,000-page Black High Yield Cartridge, 34,000-page Colour (CMY) High Yield Cartridges

Photoconductor Estimated Yield

Up to 100000 Black / 90000 (CMY) pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

18,500-page Black Toner Cartridge, 11,500-page Colour (CMY) Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Package Size (mm - H x W x D)

1505 x 758 x 911 mm

Packaged Weight, kg

168 kg

Size (mm - H x W x D)

1225 x 615 x 792 mm

Weight

134.5 kg

Size, Trays Extended (mm - H x W x D)

1553 x 953 x 1246 mm

Noise level (Idle mode)

28 dBA

Noise Level (Print), Operating

55 dBA

Duplex Print Noise Level, Operating

55 dBA

Noise Level (Copy), Operating

57 dBA

Noise Level (Scan), Operating

53 dBA

Quiet Mode

50 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

1.22 watts

Average Power (Ready Mode)

230 watts

Average Power (Printing)

1250 watts

Average Power while Printing Duplex

1250 watts

Average Power (Copying)

1275 watts

Average Power (Scanning)

250 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

1.29 kilowatt-hours per week

Product Guarantee

1-Year Onsite Service, Next Business Day

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SII, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT Gold, Blue Angel (Blauer Engel), China Green Product (CGP)

Maximum Monthly Duty Cycle

Up to 300000 pages per month³

Recommended Monthly Page Volume

8000 - 50000 pages²

Specified Operating Environment

Altitude: 0 - 2500 Metres (8,200 Feet), Humidity: 15 to 85% Relative Humidity, Temperature: 10 to 30°C (50 to 86°F)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

Developer Unit(s) Estimated Yield

Up to 600000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)


²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



P/N	Toner Cartridges	P/N	Paper Handling	P/N	Extended Warranties
76C00C0	Lexmark CS/CX921, 923, CX922, 924 Cyan 11.5K Toner Cartridge	26Z0080	MS911, MX91x Staple Punch Finisher (4-Hole)	2361737	CX924 2-Years Total Onsite Service, Next Business Day
76C00M0	Lexmark CS/CX921, 923, CX922, 924 Magenta 11.5K Toner Cartridge			2361738	CX924 3-Years Total Onsite Service, Next Business Day
76C00Y0	Lexmark CS/CX921, 923, CX922, 924 Yellow 11.5K Toner Cartridge	P/N	Furniture	2361739	CX924 4-Years Total Onsite Service, Next Business Day
76C00K0	Lexmark CS/CX921, 923, CX922, 924 Black 18.5K Toner Cartridge	32C0053	Cabinet with casters	2361740	CX924 5-Years Total Onsite Service, Next Business Day
76C0HC0	Lexmark CS/CX923, CX921, 922, 924 Cyan 34K Toner Cartridge	26Z0090	Working Shelf	2361741	CX924 1-Year Onsite Service Renewal, Next Business Day
76C0HM0	Lexmark CS/CX923, CX921, 922, 924 Magenta 34K Toner Cartridge	P/N	Memory Options	2361742	CX924 1-Year Post Wty Onsite Repair NBD Warranty
76C0HY0	Lexmark CS/CX923, CX921, 922, 924 Yellow 34K Toner Cartridge	27X0400	500+ GB Hard Disk	2367447	CX924 7 Years Total (1+6) Onsite Repair Next Business Day
86C0HK0	Lexmark CX921, 922, 923, 924 Black 34K Toner Cartridge	57X9020	2GB x32 DDR3 RAM	2365941	CX924 6 Years Total (1+5) Onsite Repair Next Business Day
76C0PK0	Lexmark CS/CX921, 923, CX922, 924, C9235, XC9235, 9245, 9255, 9265 1-Pack 100K Photoconductor	57X9812	Simplified Chinese Font Card	2365942	CX924 2 Years renewal OnSite Service, Response Time Next Business Day
76C0PV0	Lexmark CS/CX921, 923, CX922, 924, C9235, XC9235, 9245, 9255, 9265 1-Pack C, M, or Y 90K Photoconductor	57X9810	Traditional Chinese Font Card	2365943	CX924 3 Years renewal OnSite Service, Response Time Next Business Day
25A0013	Staple Cartridges (3 pack)	57X9101	256MB Flash Memory Card	2365944	CX924 4 Years renewal OnSite Service, Response Time Next Business Day
54G0W00	Lexmark MS/MX911, MX910, 912 90K Waste Container	P/N	Application Solutions		
		40C9201	Card for IPDS		
		40C9200	Forms and Bar Code Card		
		40C9202	Card for PRESCRIBE Emulation		
		57X0300	Contact Authentication Device		
		57X0301	Contactless Authentication Device		
		57X0210	Elatec Reader Authentication Device		
		P/N	Connectivity		
		27X0142	Lexmark MarkNet™ N8230 Fiber Ethernet Print Server		
		27X6510	MarkNet N8370 802.11 a/b/g/n/ac Wireless Print Server		
		1021231	Parallel (10') Cable	P/N	User Replaceable Parts
		1021294	USB (2 Meter) Cable	41X1505	Fuser
		14F0100	RS-232C Serial Interface Card	P/N	Service Parts
		14F0000	Parallel 1284-B Interface Card	41X1594	CMY Developer unit Maintenance Kit
		27X0225	MarkNet N8350 802.11b/g/n Wireless Print Server	41X1592	ADF Maintenance Kit
		SPD0002	Surge Protective Device, 220-240V		