



Lexmark MS421dw

Strike the perfect balance of performance and affordability in small-workgroup mono printing with the up to 40-pages-per-minute* Lexmark MS421dw, featuring standard two-sided printing, enhanced security and standard Wi-Fi.

Part Number

36S0230

Print Technology

Black & White Laser Printer

Workgroup Size

Small Workgroup

Touch Screen Display

No

Display

2-line 128 x 32 pixel All Points Addressable (APA) monochrome OLED display

Print Speed (A4, Black)

Do 40 ppm⁶

Hitrost tiskanja (A4, Črno) Duplex

Do 20 spm⁶

Time to First Page (Black) As fast as

Hitrost: 6.25 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 300 x 300 dpi, 600 x 600 dpi

Processor Speed

1.0 GHz

Memory, Standard

512 MB

Memory, Maximum

512 MB

Hard Disk

Not Available

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Podprti Linux operacijski sistemi

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 16.04 LTS, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

Podprti Microsoft Windows operacijski sistemi

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3

Podprti UNIX operacijski sistemi

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

250-Sheet Input, 100-Sheet Multipurpose Feeder, 150-Sheet Output Bin, Integrated Duplex

Optional Paper Handling

250-Sheet Tray, 550-Sheet Tray, 550-Sheet Lockable Tray

Paper Input Capacity, Standard

Do 350 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 900 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 150 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 150 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 120 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 216 gsm

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

3

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Connectivity

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), 802.11b/g/n Wireless

Direct USB

No

Ethernet Network

Yes

Wireless

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Enhanced IP (Port 9400), FTP, TFTP, ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPsec

Printable Area (metric)

4.0 mm zgornjih, spodnjih, desni in levih robov (znotraj)

Printer Languages (Standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 91 scalable PostScript fonts

Laser Cartridge Yields (up to)⁵

6,000-page Cartridge, 15,000-page High Yield Cartridge, 20,000-page Extra High Yield Cartridge,

Imaging Unit Estimated Yield

Do 60000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

3,000-page Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

376 x 430 x 470 mm

Packaged Weight, kg

15.81 kg

Size (mm - H x W x D)

260 x 399 x 374 mm

Weight

14.0 kg

Noise level (Idle mode)

14 dBA

Noise Level (Print), Operating

55 dBA

Duplex Print Noise Level, Operating

54 dBA

Quiet Mode

52 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.1 watts

Average Power (Sleep Mode)

1.56 watts

Average Power (Ready Mode)

7.5 watts

Average Power (Printing)

570 watts

Average Power while Printing Duplex

345 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

0.58 kilowatt-hours per week

Garancija izdelka

1-Year Return-to-Base Service

Product Certifications

ENERGY STAR, ICES-003 Class B, BSMI Class B, VCCI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, Wi-Fi CERTIFIED?, China Green Product (CGP)

Maximum Monthly Duty Cycle

Do 100000 Strani na mesec³

Recommended Monthly Page Volume

1000 - 10000 Strani²

Specified Operating Environment

Temperature: 16 to 32°C (60 to 90°F),

Humidity: 8 to 80% Relative Humidity, Altitude:

0 - 5000 Meters (16,404 Feet)

License/Agreement Terms

Printers are sold subject to certain license/agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

US/Canada/LV LAD - Mexico, LA HV, AP &

EMEA - PRC

UNSPSC Code

43212105

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average standard page yield value declared in accordance with ISO/IEC 19752.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

P/N	Kartuše z barvilom	P/N	Podaljšane garancije
56FOXA0	Lexmark 56FOXA0 Black Extra High Yield Toner Cartridge	2364561	MS421 4-Year Onsite Service Renewal
56F2000	Lexmark 56F2000 Black Return Program Toner Cartridge	P/N	Deli, ki jih lahko zamenja uporabnik
56F2X00	Lexmark 56F2X00 Black Extra High Yield Return Program Toner Cartridge	41X0918	Pick Tire
56F0ZA0	Lexmark 56F0ZA0 Black Imaging Unit		
56F0Z00	Lexmark 56F0Z00 Black Return Program Imaging Unit		
56F2H00	Lexmark 56F2H00 Black High Yield Return Program Toner Cartridge		
56F2H0E	Lexmark 56F2H0E Black High Yield Corporate Toner Cartridge		
56F2X0E	Lexmark 56F2X0E Black Extra High Yield Corporate Toner Cartridge		
56F0Z0E	Lexmark 56F0Z0E Corporate Imaging Unit		
P/N	Ravnanje s papirjem		
36S2910	250-Sheet Tray		
36S3110	550-Sheet Tray		
36S3120	550-Sheet Lockable Tray		
P/N	Pohištvo		
35S8502	Adjustable Stand		
P/N	Možnosti pomnilnika		
57X9801	256MB Flash Memory Card		
57X9814	Korean Font Card		
57X9815	Japanese Font Card		
57X9812	Simplified Chinese Font Card		
57X9810	Traditional Chinese Font Card		
P/N	Možnosti povezovanja		
SPD0002	Surge Protective Device, 220-240V		
P/N	Podaljšane garancije		
2361891	MS421 2-Years Total (1+1) Return-to-Base, 5-7 Business Days		
2361892	MS421 3-Years Total (1+2) Return-to-Base, 5-7 Business Days		
2361893	MS421 4-Years Total (1+3) Return-to-Base, 5-7 Business Days		
2361894	MS421 5-Years Total (1+4) Return-to-Base, 5-7 Business Days		
2361895	MS421 1-Year Return-to-Base Renewal, 5-7 Business Days		
2361896	MS421 1-Year Post Warranty Return-to-Base, 5-7 Business Days		
2361898	MS421 Upgrade to Onsite Service		
2361899	MS421 2-Years Total (1+1) Onsite Service		
2361900	MS421 3-Years Total (1+2) Onsite Service		
2361901	MS421 4-Years Total (1+3) Onsite Service		
2361902	MS421 5-Years Total (1+4) Onsite Service		
2361903	MS421 1-Year Onsite Service Renewal		
2361904	MS421 1-Year Post Wty OSR NBD Ext Warranty		
2364554	MS421 6-Years Total (1+5) Return-to-Base, 5-7 Business Days		
2364558	MS421 6-Years Total (1+5) Onsite Service		
2364555	MS421 2-Year Return-to-Base Renewal, 5-7 Business Days		
2364556	MS421 3-Year Return-to-Base Renewal, 5-7 Business Days		
2364557	MS421 4-Year Return-to-Base Renewal, 5-7 Business Days		
2364559	MS421 2-Year Onsite Service Renewal		
2364560	MS421 3-Year Onsite Service Renewal		