

# Lexmark MX522adhe

Get performance plus the durability of long-life components with the MX522adhe, the fax-equipped, up to 44 pages-perminute\* multifunction product with standard hard drive.

#### **Part Number**

36S0850

#### Print technology

Black & White Laser Printer

#### Functionality

Colour Scanning, Copying, Faxing, Network Scanning, Printing

#### Workgroup size

Medium-Large Workgroup

#### Touch screen display

Yes

# Display

Lexmark e-Task 4.3-inch (10.9 cm) colour touch screen

#### Print speed (A4, black)

Up to 44 ppm<sup>6</sup>

#### Print speed (A4, black) duplex

Up to 23 spm<sup>6</sup>

# Time to first page (black)

As fast as 6 seconds

# Duplex (2-sided) printing

Integrated Duplex

#### Print resolution, black

1200 IQ (1200 x 600 dpi), 1200 x 1200 dpi, 2400 IQ (2400 x 600 dpi), 600 x 600 dpi

# Copy speed (A4, black)

Up to 44 cpm<sup>6</sup>

#### Copy speed (A4, black) duplex

Up to 23 spm<sup>6</sup>

# Time to first copy (black)

As fast as 6 seconds

#### Reduce / enlarge range

25 - 400 %

#### Simplex scan speed (A4, black)

Up to 42 / 45 spm

# Simplex scan speed (A4, colour)

Up to 22 / 24 spm

# Duplex scan speed (A4, black)

Up to 84 / 90 spm

# Duplex scan speed (A4, colour)

Up to 44 / 48 spm

# Scan area, maximum

215.9 x 355.6 mm

# ADF scan

DADF (single pass Duplex)

# Scanner type

Flatbed scanner with ADF

#### Scan technology

CIS

### Optical scan resolution

600 X 600 dpi (black), up to 600 X 600 ppi (colour)

#### Scan file formats (send as)

JPEG, JPG, PDF, Secure PDF, TIFF, Archival PDF (A-1a, A-1b), Searchable PDF (optional OCR with 1GB RAM and hard disk required), Highly compressed PDF (1GB RAM and hard disk required)

#### Scan destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer, Lexmark Document Solutions Suite (LDSS)

#### Modem speed

ITU T.30, V.34 Half-Duplex, 33.6 kbps

#### **Processor speed**

Quad Core, 1.2 GHz

# Memory, standard

2048 MB

# Memory, maximum

2048 MB

#### **Hard Disk**

Included in configuration

#### Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11, 10.12, 10.13)

#### Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0., Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0, Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

# Linux operating systems supported

Debian GNU/Linux 7.0, 8.0, SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 13.2, Fedora 23, 24, Red Hat Enterprise Linux WS 6, 7, openSUSE Linux 42.3

# Microsoft Windows operating systems supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10

# Novell operating systems supported

Novell NetWare 6.5 Open Enterprise Server, Novell NetWare 5.1(SP 6+), 6.0(SP 3+) with Novell Distributed Print Services (NDPS), Novell Open Enterprise Server on SUSE Linux Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11, Novell Open Enterprise Server 2 SP2 on SuSE Linux Enterprise Server 10 SP3 3

#### **UNIX** operating systems supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

#### Standard paper handling

250-sheet input, 100-Sheet Multipurpose Feeder, 150-sheet output bin, Integrated Duplex

#### Optional paper handling

250-Sheet Tray, 550-Sheet Tray, 550-Sheet Lockable Tray

# Paper input capacity, standard

Up to 350 pages

#### Paper input capacity, maximum

Up to 2000 pages

#### Paper output capacity, standard

Up to 150 pages

# Paper output capacity, maximum

Up to 150 pages

# Paper weight range supported - standard

tray

60 - 120 g/m<sup>2</sup>

# Autom. document feeder (ADF)

50-sheet autom. document feeder

#### ADF paper input capacity

Up to 50 pages

#### ADF paper output capacity

Up to 50 pages

# Finishing

No

# Number of paper inputs, standard

-

# Number of paper inputs, maximum 5

5

# Media types supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Transparencies, Refer to the Paper & Specialty Media Guide

# Media sizes supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

#### Standard connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear USB 2.0 Hi-Speed certified port (type A)

#### Optional local ports

Internal RS-232C serial, Internal 1284-B Bidirectional Parallel

#### Optional network ports

Marknet N8372 WiFi Option

#### **Direct USB**

Yes

#### Ethernet network

Yes

#### Wireless

Wireless Option

# Network protocol support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

#### **Network printing methods**

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

#### Network management protocols<sup>1</sup>

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Telnet, Finger,

### **Network security**

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

#### Printable area

4.0 mm of the top, bottom, right and left edges (within)

#### Printer languages (standard)

PCL 5e Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, AirPrint™, PDF 1.7 emulation

#### Fonts and symbol sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 91 scalable PostScript fonts

#### Cartridge yields: up to<sup>5</sup>

6000-page cartridge, 15,000-page High Yield Cartridge, 20.000-page cartridge, , 25.000page Ultra High Yield Cartridge

#### Imaging unit yield

Up to 60000 pages, based on average 3 pages per print job and 5% coverage<sup>4</sup>

### Cartridge(s) shipped with product

6000-page starter Return Programme toner

# Replacement cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

#### Packaged size (HxWxD)

614 x 511 x 576 mm

# Packaged weight

23.90 ka

#### Size (HxWxD)

477 x 489 x 429.5 mm

#### Weight

20.6 kg

# Noise level, idle

14 dBA

# Noise Level (Print), Operating

56 dBA

# Duplex print noise level, operating

55 dBA

#### Noise Level (Copy), Operating 56 dBA

# Noise Level (Scan), Operating

55 dBA

#### Quiet mode

51 dBA

# **Energy Star**

# Average power in Hibernate mode

0.1 Watt

# Average power in Sleep mode

1.41 Watt

#### Average power in Ready mode

14.5 Watt

# Average power while printing

620 Watt

#### Average power while printing duplex

385 Watt

#### Average power while copying

630 Watt

#### Average power while scanning

20 Watt

#### **Energy Star Typical Electricity Consumption** (TEC)

0.63 kWh per week

#### Product quarantee

1-Year Onsite Service, Next Business Day

#### **Product certifications**

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, US FDA, UL 60950-1, FCC Class A, cUL CAN/CSA-C22.2 60950-1, NOM, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class A, EuP, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, EC 1275, MET-I, ISO 532B, ECMA-370, TED, GOST-R, SII, TER, China Green Product (CGP)

#### Maximum monthly duty cycle

Up to 120000 pages per month<sup>3</sup>

#### Recommended monthly page volume

2000 - 15000 pages<sup>2</sup>

#### Specified operating environment

Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 5000 Meters

### **License/Agreement Terms**

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

# Country of origin

US/Canada/LV LAD - Mexico, LA HV, AP & EMEA - PRC

# **UNSPSC** code

43212110

<sup>&</sup>lt;sup>1</sup>This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http:// www.openssl.org/)

 $<sup>^2\</sup>mbox{\tt "Recommended Monthly Page Volume"}$  is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

<sup>&</sup>lt;sup>3</sup>"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs

<sup>&</sup>lt;sup>4</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

<sup>&</sup>lt;sup>5</sup>Average standard page yield value declared in accordance with ISO/IEC 19752.

<sup>&</sup>lt;sup>6</sup>Print and copy speeds measured in accordance with ISO/ IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds





Callout	<b>Availability</b>	Description
1	Standard	10.9 cm (4.3-inch) Touch Screen
2	Standard	100-Sheet Multipurpose Feeder
3	Standard	250-Sheet Input
4	Optional	250-Sheet Tray / 550-Sheet Tray

P/N	Toner Cartridges	P/N	Extended Warranties
56F0UA0	Lexmark MS/MX521, 622, MX522,	2362171	MX522 1-Year Onsite Service
56F2000	MS621 25K Toner Cartridge Lexmark MS/MX321, 421, 521, 622,	2362172	Renewal MX522 1 Year Post Warranty Onsite
	MX522, MS621 Return Programme 6K Toner Cartridge	2362173	Repair NBD Warranty MX522 Per Call 1-Time NBD On Site
56F2X00	Lexmark MS/MX421, 521, 622, MS621, MX522 Return Programme	2362174	Repair Warranty MX522 Upgrade to Onsite Service
F.C.F.21.10.0	20K Toner Cartridge		NBD Fix
56F2U00	Lexmark MS/MX521, 622, MX522, MS621 Return Programme 25K Toner		MX522 1-Year Onsite Service NBD Fix
56F0ZA0	Cartridge Lexmark MS/MX321, 421, 521, 622,	2362177	MX522 2-Year Onsite Service NBD Fix
	MX522, MS621, B/MB2338, 2442, 2546, 2650, M/XM1242, 1246, 3250	2362178	MX522 3-Year Onsite Service NBD Fix
56F0Z00	60K Imaging Unit MS/MX32x, 42x, 52x, 62x, M/XM12xx,	2362179	MX522 4-Year Onsite Service NBD Fix
	32xx, B/MB2x Return Programme 60K Imaging Unit	2362180	MX522 1-Year Renewal Onsite Service NBD Fix
56F2H00	Lexmark MS/MX321, 421, 521, 622,	2365275	MX522 6-Years Total (1+5) Onsite
	MS621, MX522 Return Programme 15K Toner Cartridge	2367254	Service MX522 7-Years Total (1+6) Onsite
56F2H0E	Lexmark MS/MX321, 421, 521, 622, MS621, MX522 Corporate 15K Toner	2369264	Service MX522 5-Year Onsite Service NBD
56F2X0E	Cartridge Lexmark MS/MX421, 521, 622,	2369265	Fix MX522 6-Year Onsite Service NBD
301 27(32	MS621, MX522 Corporate 20K Toner		Fix MX522 Per Call Prev Maint, with Kit
56F2U0E	Cartridge Lexmark MS/MX521, 622, MX522,	2362196 2365276	MX522 Per Call Prev Maint. With Kit MX522 2-Year Onsite Service
	MS621 Corporate 25K Toner		Renewal
56F0Z0E	Cartridge Lexmark MS/MX321, 421, 521, 622,	2365277	MX522 3-Year Onsite Service Renewal
	MX522, MS621, B/MB2338, 2442, 2546, 2650, M/XM1242, 1246, 3250	2365278	MX522 4-Year Onsite Service Renewal
	Corporate 60K Imaging Unit	2365279	MX522 2-Year Renewal Onsite
P/N	Paper Handling	2365280	Service NBD Fix MX522 3-Year Renewal Onsite
36S2910	250-Sheet Tray		Service NBD Fix
36S3110	550-Sheet Tray	2365281	MX522 4-Year Renewal Onsite
36S3120	550-Sheet Lockable Tray		Service NBD Fix
P/N	Furniture		
3073173	Swivel cabinet (25 cm, incl. storage)	•	
35S8502	Printer Stand (adjustable height)		
P/N	Memory Options		
57X9801	256 MB Flash Memory Card	-	
P/N	Application Solutions	_	
40C9201	IPDS Card		
	Forms and Bar Code Card		
	Prescribe Card		
57X0185	Lexmark Secure Element		
P/N	Connectivity	-	
27X6410	Lexmark MarkNet N8372 802.11 a/b/ g/n/ac Wireless Print Server		
27X0912	Lexmark MarkNet™ N8230 Fiber		
	Ethernet Print Server		
57X7040	English Keyboard Kit		
1021231	Parallel Cable (IEEE 1284 A-B, 3 meter)		
1021294	USB Cable (2 meter)		
27X0901	MS610de, MX51x, MX611 Parallel		
27X0900	1284-B Interface Card MS610de, MX51x, MX611 RS-232C		
2770300	Serial Interface Card		
SPD0002	Surge protective device		
P/N	Extended Warranties		
2362167	MX522 2-Years Total (1+1) Onsite Service	-	
2362168	MX522 3-Years Total (1+2) Onsite		
2362169	Service MX522 4-Years Total (1+3) Onsite		
2362170	Service MX522 5-Years Total (1+4) Onsite		
2002170	Service		