



Lexmark CS725de

Faster printing, heavier workloads and longer service intervals join lower cost per page in the durable, easy-to-use, feature-rich Lexmark CS725de.

Part Number

40C9036

Print Technology

Colour Laser

Function

Colour Printing

Workgroup Size

Medium-Large Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen

Print Speed (A4, Black)

Do 47 ppm⁶

Print Speed (A4, Colour)

Do 47 ppm⁶

Hitrost tiskanja (A4, Črno) Duplex

Do 38 spm⁶

Time to First Page (Black) As fast as

Hitrost: 5.4 sekund

Time to First Page (Colour) As fast as

Hitrost: 5.7 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Processor Speed

Quad Core, 1.2 GHz

Memory, Standard

1024 MB

Memory, Maximum

3072 MB

Hard Disk

Option available

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11)

Citrix MetaFrame

Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Podprti Linux operacijski sistemi

Debian GNU/Linux 7.0, 8.0, Fedora 21, 22, Linpus Linux Lite Desktop 2.1, Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS, Linux Mint 2 Debian, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 4, 5, 6, 7, SUSE Linux Enterprise Desktop 10, 11, 12, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 12.04 LTS, 14.04 LTS, 15.04, openSUSE 13.1, 13.2, openSUSE Tumbleweed

Podprti Microsoft Windows operacijski sistemi

Windows XP, Windows XP x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11

Podprti UNIX operacijski sistemi

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin

Optional Paper Handling

550-Sheet Tray

Paper Input Capacity, Standard

Do 650 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 2300 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 300 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 300 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 218 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 218 gsm

Integrated Tray Card Stock Upper limit (grain long)

Index Bristol - 199 gsm (110 lb), Tag - 163 gsm (100 lb), Cover - 176 gsm (65 lb)

Integrated Tray Card Stock Upper limit (grain short)

Index Bristol - 199 gsm (110 lb), Cover - 216 gsm (80 lb), Tag - 203 gsm (125 lb)

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Banner Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

No

Standard Connectivity

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A)

Optional Network Ports

Internal MarkNet N8360 802.11b/g/n Wireless, NFC

Direct USB

Yes

Ethernet Network

Yes

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4, AppleTalk™, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, Microsoft XPS (XML Paper Specification), AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 165 scalable PostScript fonts, 15 PPDS bitmap fonts

Laser Cartridge Yields (up to)⁵

, 3,000-page Black and Colour (CMYK) Cartridges, 7,000-page Black and Colour (CMYK) Cartridges, 12,000-page Colour (CMY) High Yield Cartridges, 20,000-page Black High Yield Cartridge

Imaging Unit Estimated Yield

Do 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

7,000-page Black and Colour (CMYK) Return Program Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

568 x 643 x 738 mm

Packaged Weight, kg

41.9 kg

Size (mm - H x W x D)

417 x 475 x 499 mm

Weight

36.3 kg

Noise level (Idle mode)

15 dBA

Noise Level (Print), Operating

53 dBA

Duplex Print Noise Level, Operating

55 dBA

Quiet Mode

47 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.3 watts

Average Power (Sleep Mode)

2.23 watts

Average Power (Ready Mode)

80 watts

Average Power (Printing)

680 watts

Average Power while Printing Duplex

570 watts

ENERGY STAR Typical Electricity Consumption (TEC)

0.86 kilowatt-hours per week

Garancija izdelka

1-Year Onsite Service

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SIL, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, China Green Product (CGP)

Maximum Monthly Duty Cycle

Do 150000 Strani na mesec³

Recommended Monthly Page Volume

2000 - 20000 Strani²

Specified Operating Environment

Humidity: 15 to 80% Relative Humidity,
Temperature: 10 to 32°C (50 to 90°F), Altitude:
0 - 2896 Meters (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)



²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



P/N	Kartuše z barvilom	P/N	Kartuše z barvilom	P/N	Kartuše z barvilom
74C20C0	CS720, CS725, CX725 Cyan Return Program Toner Cartridge	74C2HK0	CS720, CS725 Black High Yield Return Program Toner Cartridge	74C2SKE	CS720, CS725, CX725 Black Standard Yield Corporate Cartridge (7K)
74C20M0	CS720, CS725, CX725 Magenta Return Program Toner Cartridge	74C0H10	CS720, CS725 Black High Yield Toner Cartridge	74C2SCE	CS720, CS725, CX725 Cyan Standard Yield Corporate Cartridge (7K)
74C20Y0	CS720, CS725, CX725 Yellow Return Program Toner Cartridge	74C0H20	CS725 Cyan High Yield Toner Cartridge	74C2SME	CS720, CS725, CX725 Magenta Standard Yield Corporate Cartridge (7K)
74C20K0	CS720, CS725, CX725 Black Return Program Toner Cartridge	74C0H30	CS725 Magenta High Yield Toner Cartridge	74C2SYE	CS720, CS725, CX725 Yellow Standard Yield Corporate Cartridge (7K)
74C2SC0	CS720, CS725, CX725 Cyan Standard Yield Return Program Toner Cartridge	74C0H40	CS725 Yellow High Yield Toner Cartridge	74C2HKE	CS720, CS725 Black High Yield LRP Corporate Cartridge (20K)
74C2SM0	CS720, CS725, CX725 Magenta Standard Yield Return Program Toner Cartridge	74C0Z10	CS720, CS725, CX725 Black Imaging Unit	74C2HCE	CS725 Cyan High Yield Corporate Cartridge (12K)
74C2SY0	CS720, CS725, CX725 Yellow Standard Yield Return Program Toner Cartridge	74C0ZK0	CS720, CS725, CX725 Black Return Program Imaging Unit	74C2HME	CS725 Magenta High Yield Corporate Cartridge (12K)
74C2SK0	CS720, CS725, CX725 Black Standard Yield Return Program Toner Cartridge	74C0ZV0	CS720, CS725, CX725 Colour (CMY) Return Program Imaging Kit	74C2HYE	CS725 Yellow High Yield Corporate Cartridge (12K)
74C2HC0	CS725 Cyan High Yield Return Program Toner Cartridge	74C0Z50	CS720, CS725, CX725 Colour (CMY) Imaging Kit	74C0W00	Waste Toner Bottle
74C2HM0	CS725 Magenta High Yield Return Program Toner Cartridge	74C20KE	CS720, CS725, CX725 Black Corporate Cartridge (3K)		
74C2HY0	CS725 Yellow High Yield Return Program Toner Cartridge	74C20CE	CS720, CS725, CX725 Cyan Corporate Cartridge (3K)	P/N	Ravnanje s papirjem
		74C20ME	CS720, CS725, CX725 Magenta Corporate Cartridge (3K)	40C2100	550-Sheet Tray
		74C20YE	CS720, CS725, CX725 Yellow Corporate Cartridge (3K)	P/N	Pohištvo
				40C2300	Adjustable Stand

P/N	Možnosti pomnilnika
27X0400	500+ GB Hard Disk
57X9020	2GB x32 DDR3 RAM
57X9801	256MB Flash Memory Card
57X9814	Korean Font Card
57X9815	Japanese Font Card
57X9812	Simplified Chinese Font Card
57X9810	Traditional Chinese Font Card

P/N	Programske rešitve
40C9201	Card for IPDS
40C9200	Forms and Bar Code Card
40C9202	Card for PRESCRIBE Emulation
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device
57X0210	Elatec Reader Authentication Device
57X0250	Elatec TWN4 MultiTech-P LEGIC 42 Kit Bosch-SPR000264

P/N	Možnosti povezovanja
27X0802	CS72X, CX72x Lexmark MarkNet™ N8230 Fiber Ethernet Print Server
27X0823	MarkNet N8370 Wireless for CS720, CS725, CX725
SPD0002	Surge Protective Device, 220-240V

P/N	Podaljšane garancije
2360121	CS725 2-Years Total (1+1) Onsite Service
2360122	CS725 3-Years Total (1+2) Onsite Service
2360123	CS725 4-Years Total (1+3) Onsite Service
2360124	CS725 5-Years Total (1+4) Onsite Service
2360125	CS725 1-Year Onsite Service Renewal
2367199	CS725,C4150 7 Years Total (1+6) Onsite Repair Next Business Day
2360860	CS725 3 Year Upgrade from Initial to Next Business Day extended Guarantee
2365064	CS725,C4150 6 Years Total (1+5) Onsite Repair Next Business Day
2365065	CS725,C4150 2 Years renewal OnSite Service, Response Time Next Business Day
2365066	CS725,C4150 3 Years renewal OnSite Service, Response Time Next Business Day
2365067	CS725,C4150 4 Years renewal OnSite Service, Response Time Next Business Day

P/N	Deli, ki jih lahko zamenja uporabnik
41X0556	Fuser Maintenance Kit 220-240V, Type 01
41X0253	Fuser 220-240V, Type 01
41X0374	Separator Bracket Assembly

P/N	Nadomestni deli
40X9929	Image Transfer Unit