



Lexmark CS720de

The Lexmark CS720de offers workgroup-level printing performance in a simple, feature-rich package that's as easy to use as a personal output device.

Part Number

40C9150

Print Technology

Colour Laser

Function

Colour Printing

Workgroup Size

Medium Workgroup

Touch Screen Display

Yes

Display

Lexmark e-Task 10.9 cm (4.3-inch) colour touch screen

Print Speed (A4, Black)

Up to 38 ppm⁶

Print Speed (A4, Colour)

Up to 38 ppm⁶

Print Speed (A4, Black) Duplex

Up to 30 spm⁶

Time to First Page (Black)

As fast as 6.0 seconds

Time to First Page (Colour)

As fast as 6.5 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

1200 x 1200 dpi, 4800 CQ (2400 x 600 dpi)

Processor Speed

Quad Core 1.2 GHz

Memory, Standard

1024 MB

Memory, Maximum

3072 MB

Hard Disk

Option available

Apple Operating Systems Supported

Apple OS X (10.6, 10.7, 10.8, 10.9, 10.10, 10.11)

Citrix MetaFrame

Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

Debian GNU/Linux 7.0, 8.0, Fedora 21, 22, Linpus Linux Lite Desktop 2.1, Linux Mint 13 LTS, 17 LTS, 17.1 LTS, 17.2 LTS, Linux Mint 2 Debian, PCLinuxOS 2014.12, Red Hat Enterprise Linux WS 4, 5, 6, 7, SUSE Linux Enterprise Desktop 10, 11, 12, SUSE Linux Enterprise Server 10, 11, 12, Ubuntu 12.04 LTS, 14.04 LTS, 15.04, openSUSE 13.1, 13.2, openSUSE Tumbleweed

Microsoft Windows Operating Systems Supported

Windows XP, Windows XP x64, Windows Vista, Windows Vista x64, Windows Server 2008, Windows Server 2008 x64, Windows 7, Windows 7 x64, Windows Server 2008 R2, Windows 8, Windows 8 x64, Windows Server 2012, Windows 8.1, Windows 8.1 x64, Windows Server 2012 R2, Windows RT, Windows RT 8.1, Windows 10

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 on SUSE Linux Enterprise Server 11

UNIX Operating Systems Supported

Sun Solaris x86 10, 11, Sun Solaris SPARC 10, 11, IBM AIX 6.1, 7.1

Included Paper Handling

550-Sheet Input, 100-Sheet Multipurpose Feeder, Integrated Duplex, 300-Sheet Output Bin

Optional Paper Handling

550-Sheet Tray

Paper Input Capacity, Standard

Up to 650 pages 75 gsm bond

Paper Input Capacity, Maximum

Up to 2300 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 300 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 300 pages 75 gsm bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 218 gsm

Paper Weight Range Supported - Multipurpose Feeder (gsm)

60 - 218 gsm

Integrated Tray Card Stock Upper limit (grain long)

Index Bristol - 199 gsm (110 lb), Tag - 163 gsm (100 lb), Cover - 176 gsm (65 lb)

Integrated Tray Card Stock Upper limit (grain short)

Index Bristol - 199 gsm (110 lb), Cover - 216 gsm (80 lb), Tag - 203 gsm (125 lb)

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

5

Media Types Supported

Card Stock, Envelopes, Paper Labels, Plain Paper, Vinyl Labels, Banner Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Caster Base

No

Standard Ports

One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A), Rear Hi-Speed USB port Compatible with USB 2.0 Specification (Type A)

Optional Network Ports

Internal MarkNet N8360 802.11b/g/n Wireless, NFC

Direct USB

Yes

Ethernet Network

Yes

Wireless

Wireless Option

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

LPR/LPD, Direct IP (Port 9100), Enhanced IP (Port 9400), Secure IP (Port 96xx), FTP, TFTP, ThinPrint .print integration, Telnet, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD, Pull Printing

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutolP), DHCP, ICMP, DNS, Bonjour, DDNS, mDNS, ARP, NTP, Telnet, Finger,

Network Security

SNMPv3, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printer Languages (Standard)

PCL 5c Emulation, PCL 6 Emulation, Personal Printer Data Stream (PPDS), PostScript 3 Emulation, Direct Image, AirPrint™, PDF 1.7 emulation

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, 39 scalable PPDS fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 165 scalable PostScript fonts, 15 PPDS bitmap fonts

Laser Cartridge Yields (up to)⁵

, 3,000-page Black and Colour (CMYK) Cartridges, 7,000-page Black and Colour (CMYK) Cartridges, 20,000-page Black High Yield Cartridge

Imaging Unit Estimated Yield

Up to 150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage⁴

Cartridge(s) Shipping with Product

3,000-page Black and Colour (CMYK) Return Programme Toner Cartridges

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

568 x 643 x 738 mm

Packaged Weight, kg

41.9 kg

Size (mm - H x W x D)

417 x 475 x 499 mm

Weight

36.3 kg

Noise level (Idle mode)

15 dBA

Noise Level (Print), Operating

51 dBA

Duplex Print Noise Level, Operating

53 dBA

Quiet Mode

47 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

0.2 watts

Average Power (Sleep Mode)

2.35 watts

Average Power (Ready Mode)

80 watts

Average Power (Printing)

560 watts

Average Power while Printing Duplex

470 watts

ENERGY STAR Typical Electricity Consumption (TEC)

0.76 kilowatt-hours per week

Product Guarantee

1-Year Onsite Service

Product Certifications

ENERGY STAR, ICES-003 Class A, BSMI Class A, VCCI Class A, FCC Class A, NOM-032, UL, cUL, NOM, US FDA/CDRH, IEC 60825-1, CB Report, ISO-532B, CE (EU) DoC, EFTA (CE), KC logo, CCC, C-tick DoC, EuP, CECP, CEL, EC 1275/2008, ECMA-370, TED, SIL, TER, SABS, UL-AR, GS Mark, Green Dot, ISO-9296, COC, CCD-035 EcoLogo, Green Mark, EPEAT, China Green Product (CGP)

Maximum Monthly Duty Cycle

Up to 120000 pages per month³

Recommended Monthly Page Volume

1500 - 15000 pages²

Specified Operating Environment

Humidity: 15 to 80% Relative Humidity,
Temperature: 10 to 32°C (50 to 90°F), Altitude:
0 - 2896 Metres (9,500 Feet)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)



²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity.

⁵Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁶Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



P/N	Toner Cartridges	P/N	Toner Cartridges	P/N	Toner Cartridges
74C50C0	CS720, CS725, CX725 Cyan Return Programme Toner Cartridge	74C0S30	CS720 Magenta Standard Yield Toner Cartridge	74C5SME	CS720, CS725, CX725 Magenta Standard Yield Corporate Cartridge (7K)
74C50M0	CS720, CS725, CX725 Magenta Return Programme Toner Cartridge	74C0S40	CS720 Yellow Standard Yield Toner Cartridge	74C5SYE	CS720, CS725, CX725 Yellow Standard Yield Corporate Cartridge (7K)
74C50Y0	CS720, CS725, CX725 Yellow Return Programme Toner Cartridge	74C0Z10	CS720, CS725, CX725 Black Imaging Unit	74C5HKE	CS720, CS725 Black High Yield LRP Corporate Cartridge (20K)
74C50K0	CS720, CS725, CX725 Black Return Programme Toner Cartridge	74C0ZK0	CS720, CS725, CX725 Black Return Programme Imaging Unit	74C0W00	Waste Toner Bottle
74C5SC0	CS720, CS725, CX725 Cyan Standard Yield Return Programme Toner Cartridge	74C0ZV0	CS720, CS725, CX725 Colour (CMY) Return Programme Imaging Kit	P/N	Paper Handling
74C5SM0	CS720, CS725, CX725 Magenta Standard Yield Return Programme Toner Cartridge	74C0Z50	CS720, CS725, CX725 Colour (CMY) Imaging Kit		
74C5SY0	CS720, CS725, CX725 Yellow Standard Yield Return Programme Toner Cartridge	74C50KE	CS720, CS725, CX725 Black Corporate Cartridge (3K)	P/N	Furniture
74C5SK0	CS720, CS725, CX725 Black Standard Yield Return Programme Toner Cartridge	74C50CE	CS720, CS725, CX725 Cyan Corporate Cartridge (3K)	40C2100	550-Sheet Tray
74C5HK0	CS720, CS725 Black High Yield Return Programme Toner Cartridge	74C50ME	CS720, CS725, CX725 Magenta Corporate Cartridge (3K)	P/N	Memory Options
74C0H10	CS720, CS725 Black High Yield Toner Cartridge	74C50YE	CS720, CS725, CX725 Yellow Corporate Cartridge (3K)		
74C0S20	CS720 Cyan Standard Yield Toner Cartridge	74C5SKE	CS720, CS725, CX725 Black Standard Yield Corporate Cartridge (7K)	27X0400	500+ GB Hard Disk
		74C5SCE	CS720, CS725, CX725 Cyan Standard Yield Corporate Cartridge (7K)	57X9020	2GB x32 DDR3 RAM
				57X9801	256MB Flash Memory Card
				57X9814	Korean Font Card
				57X9815	Japanese Font Card
				57X9812	Simplified Chinese Font Card
				57X9810	Traditional Chinese Font Card
				P/N	Application Solutions
				40C9201	Card for IPDS

P/N	Application Solutions
40C9200	Forms and Bar Code Card
40C9202	Card for PRESCRIBE Emulation
57X0300	Contact Authentication Device
57X0301	Contactless Authentication Device
57X0085	Lexmark Secure Element
57X0210	Elatec Reader Authentication Device

P/N	Connectivity
27X0802	CS72X, CX72x Lexmark MarkNet™ N8230 Fiber Ethernet Print Server
27X0823	MarkNet N8370 Wireless for CS720, CS725, CX725
1021294	USB (2 Meter) Cable

P/N	Extended Warranties
2360080	CS720 2-Years Total (1+1) Onsite Service
2360081	CS720 3-Years Total (1+2) Onsite Service
2360082	CS720 4-Years Total (1+3) Onsite Service
2360083	CS720 5-Years Total (1+4) Onsite Service
2360084	CS720 1-Year Onsite Service Renewal
2368569	CS720 7 Years Total (1+6) Next Business Day Fix
2367197	CS720 7 Years Total (1+6) Onsite Repair Next Business Day
2360088	CS720 2 Year Tota (1+1) Next Business day Fix
2360089	CS720 3 Year Tota (1+2) Next Business day Fix
2360090	CS720 4 Year Tota (1+3) Next Business day Fix
2360091	CS720 5 Year Tota (1+4) Next Business day Fix
2360092	CS720 1 Year Renewal Onsite Repair Next Business Day Fix
2360696	CS720 Per Call Preventive Maintenance with Kit
2360857	CS720 3 Year Upgrade from Initial to Next Business Day extended Guarantee
2365049	CS720 6 Year Total (1+5) Onsite Repair Next Business Day
2365050	CS720 2 Years renewal OnSite Service, Response Time Next Business Day
2365051	CS720 3 Years renewal OnSite Service, Response Time Next Business Day
2365052	CS720 4 Years renewal OnSite Service, Response Time Next Business Day
2365053	CS720 2 Year Renewal Onsite Repair Next Business Day Fix
2365054	CS720 3 Year Renewal Onsite Repair Next Business Day Fix
2365055	CS720 4 Year Renewal Onsite Repair Next Business Day Fix

P/N	User Replaceable Parts
41X0556	Fuser Maintenance Kit 220-240V, Type 01
41X0253	Fuser 220-240V, Type 01
41X0374	Separator Bracket Assembly

P/N	Service Parts
40X9929	Image Transfer Unit