

Lexmark CS331dw

The compact Lexmark CS331dw enhances your productivity with color output up to 26 [24] pages per minute*, Wi-Fi, gigabit Ethernet and high-yield replacement cartridges.

Part Number

40N9020

Print Technology

Colour Laser

Workgroup Size

Small-Medium Workgroup

Touch Screen Display

No

Display

2-line All Points Addressable (APA)
monochrome LCD display

Print Speed (A4, Black)

Do 24 ppm⁵

Print Speed (A4, Colour)

Do 24 ppm⁵

Hitrost tiskanja (A4, Črno) Duplex

Do 13 spm⁵

Hitrost tiskanja (A4, Barvno) Duplex

Do 13 spm⁵

Time to First Page (Black) As fast as

Hitrost: 10.9 sekund

Time to First Page (Colour) As fast as

Hitrost: 10.9 sekund

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

4800 CQ (2400 x 600 dpi)

Processor Speed

Dual Core, 1.0 GHz

Memory, Standard

512 MB

Memory, Maximum

512 MB

Hard Disk

Not Available

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0, Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64, Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 4.0, 4.5, Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0

Podprti Linux operacijski sistemi

SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 42.3, Fedora 27, 28, 29, Ubuntu 16.04, 18.04 LTS, Red Hat Enterprise Linux WS 6.10, 7.5, 7.6, Debian 9.4, 9.5, 9.6, Debian GNU/Linux 8.11, openSUSE Linux 15

Podprti Microsoft Windows operacijski sistemi

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 10, Windows Server 2016

Podprti Novell operacijski sistemi

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 (SP3) on SuSE Linux Enterprise Server 10 SP4 (x86 and x64) 3, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

250-Sheet Input, Integrated Duplex, Single-Sheet Manual Feed, 100-Sheet Output Bin

Paper Input Capacity, Standard

Do 250+1 strani 20 lbs ali 75 g bond

Paper Input Capacity, Maximum

Do 250+1 strani 20 lbs ali 75 g bond

Paper Output Capacity, Standard

Do 100 strani 20 lbs ali 75 g bond

Paper Output Capacity, Maximum

Do 100 strani 20 lbs ali 75 g bond

Paper Weight Range Supported - Standard Tray (gsm)

60 - 162 gsm

Finishing Option

No

Number of Paper Inputs, Standard

2

Number of Paper Inputs, Maximum

2

Media Types Supported

Card Stock, Envelopes, Gladek papir, Paper Labels, Plain Paper, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Connectivity

USB 2.0 Specification Hi-Speed Certified (Type B), 802.11b/g/n Wireless, Ethernet 10/100/1000 BaseTX (RJ-45)

Direct USB

No

Ethernet Network

Yes

Wireless

Yes

Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Načini mrežnega tiskanja

LPR/LPD, Enhanced IP (Port 9400), FTP, TFTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD

Network Management Protocols¹

HTTP, HTTPS (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Finger,

Network Security

SNMPv3, IPSec

Printable Area (metric)

4.2 mm zgornjih, spodnjih, desni in levih robov (znotraj)

Printer Languages (Standard)

PCL 5c Emulation, PCL 5e Emulation, PCL 6 Emulation, PostScript 3 Emulation, Direct Image, PCL 5, PCLm

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 91 scalable PostScript fonts, 89 scalable PCL fonts

Laser Cartridge Yields (up to)⁴

1,500-page Black and Colour (CMYK) Cartridges, , 4,500-page Black High Yield Cartridge, 4,500-page Colour (CMY) High Yield Cartridges

Cartridge(s) Shipping with Product

750-page Black Return Program Toner Cartridge, 500-page Colour (CMY) Return Program Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/ regions for more details.

Packaged Size (mm - H x W x D)

519 x 332 x 556 mm

Packaged Weight, kg

19.1 kg

Size (mm - H x W x D)

243.7 x 411.2 x 394.1 mm

Weight

16.1 kg

Noise level (Idle mode)

14 dBA

Noise Level (Print), Operating

52 dBA

Duplex Print Noise Level, Operating

51 dBA

Quiet Mode

46 dBA

ENERGY STAR

Yes

Average Power (Hibernate Mode)

NA watts

Average Power (Sleep Mode)

0.84 watts

Average Power (Ready Mode)

15 watts

Average Power (Printing)

395 watts

Average Power while Printing Duplex

275 watts

ENERGY STAR Typical Electricity**Consumption (TEC)**

0.31 kilowatt-hours per week

Garancija izdelka

1-Onsite Repair, 3 -5 Business Days

Product Certifications

ENERGY STAR, Blue Angel DE-UZ 219, ICES-003 Class B, US FDA/CDRH, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60825-1, CE DoC (EN 62311, EN 55022(Class B), EN 55024, EN 61000, EN 61000, UL), EFTA (CE), KCC, CCC, CECF, CEL, RCM DoC, UL-AR, KC mark, UL GS mark, UCRF, BSMI EMC Class B, Wi-Fi CERTIFIED, China Green Product (CGP)

Maximum Monthly Duty Cycle

Do 50000 Strani na mesec³

Recommended Monthly Page Volume

600 - 2500 Strani²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Meters (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212105

¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>)

²"Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

³"Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798.

⁵Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

P/N	Kartuše z barvilom
20N0W00	Lexmark 20N0W00 Waste Print Bottle
20N20C0	Lexmark 20N20C0 Cyan Return Program Print Cartridge
20N20M0	Lexmark 20N20M0 Magenta Return Program Print Cartridge
20N20Y0	Lexmark 20N20Y0 Yellow Return Program Print Cartridge
20N20K0	Lexmark 20N20K0 Black Return Program Print Cartridge
20N2HC0	Lexmark 20N2HC0 Cyan High Yield Return Program Print Cartridge
20N2HM0	Lexmark 20N2HM0 Magenta High Yield Return Program Print Cartridge
20N2HY0	Lexmark 20N2HY0 Yellow High Yield Return Program Print Cartridge
20N2HK0	Lexmark 20N2HK0 Black High Yield Return Program Print Cartridge
20N0H10	Lexmark 20N0H10 Black High Yield Print Cartridge
20N0H20	Lexmark 20N0H20 Cyan High Yield Print Cartridge
20N0H30	Lexmark 20N0H30 Magenta High Yield Print Cartridge
20N0H40	Lexmark 20N0H40 Yellow High Yield Print Cartridge

P/N	Pohištvo
40C2300	Adjustable Stand

P/N	Podaljšane garancije
2370813	CS331 2-Years Total (1+1) Onsite Repair Next Business Day
2370814	CS331 3-Years Total (1+2) Onsite Repair Next Business Day
2370815	CS331 4-Years Total (1+3) Onsite Repair Next Business Day
2370816	CS331 5-Years Total (1+4) Onsite Repair Next Business Day
2370817	CS331 1-Year Renew Onsite Repair Next Business Day
2370818	CS331 2-Year Renew Onsite Repair Next Business Day
2370820	CS331 Post Warranty Onsite Repair Next Business Day