

Lexmark CX431adw

Small workgroup colour versatility is easy to deploy and share with the compact, lightweight Lexmark CX431adw multifunction, offering output at up to 24 ppm*.

Part Number

40N9470

Print Technology

Colour Laser

Colour Copying, Colour Printing, Colour Scanning, Faxing

Workgroup Size

Small-Medium Workgroup

Touch Screen Display

Display

2.8 inch (7.2 cm) LCD touch panel

Print Speed (A4, Black)

Up to 24.7 ppm⁴

Print Speed (A4, Colour)

Up to 24.7 ppm⁴

Print Speed (A4, Black) Duplex

Up to 13 spm⁴

Print Speed (A4, Colour) Duplex

Up to 13 spm⁴

Time to First Page (Black)

As fast as 10.8 seconds

Time to First Page (Colour)

As fast as 11 seconds

Duplex (2-sided) Printing

Integrated Duplex

Print Resolution, Black

4800 CQ (2400 x 600 dpi)

Print Resolution, Colour

4800 CQ (2400 x 600 dpi)

Copy Speed (A4, Black)

Up to 24.7 cpm⁴

Copy Speed (A4, Colour)

Up to 24.7 cpm⁴

Copy Speed (A4, Black) Duplex

Up to 24.7 spm⁴

Copy Speed (A4, Colour) Duplex

Up to 24.7 spm⁴

Time to First Copy (Black)

As fast as 12.1 seconds

Time to First Copy (Colour)

As fast as 13.3 seconds

Reduce / Enlarge Range

25 - 400 %

A4/Ltr Simplex Scan Speed (Black)

Up to 45 / 48 sides per minute

A4/Ltr Simplex Scan Speed (Colour)

Up to 20 / 21 sides per minute A4/Ltr Duplex Scan Speed (Black)

Up to 90 / 96 sides per minute

A4/Ltr Duplex Scan Speed (Colour)

Up to 40 / 42 sides per minute

Scan Area, Maximum (mm)

216 x 356 mm

ADF Scan

DADF (single pass Duplex)

Scanner Type

Flatbed scanner with ADF

Scan Technology

Optical Scanning Resolution

600 X 600 dpi (black), up to 600 X 600 ppi

Scan File Formats (Send as)

JPEG, JPG, PDF, TIFF

Scan Destinations

e-mail, FTP, USB Flash drive, USB or Network connected computer

Modem Speed

Max is 33,600 bps, V.34 Half-Duplex Kbps

Fax Transmission Speed

< 3 seconds per page

Processor Speed

Dual Core, 1.0 GHz

Memory, Standard

Memory, Maximum

Hard Disk

Not Available

Apple Operating Systems Supported

Support is provided through AirPrint and AirScan only

Citrix MetaFrame

Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64, Microsoft Windows Server 2003 and 2003 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 and 2008 X64 Edition with Citrix XenApp 5.0, Microsoft Windows Server 2008 R2 with Citrix XenApp 6.0, 6.5, Microsoft Windows Server 2012 with Citrix XenApp 6.0, 6.5

Linux Operating Systems Supported

SUSE Linux Enterprise Server 10, 11, 12, openSUSE Linux 42.3, Fedora 27, 28, 29, Ubuntu 16.04, 18.04 LTS, Red Hat Enterprise Linux WS 6.10, 7.5, 7.6, Debian 9.4, 9.5, 9.6, Debian GNU/Linux 8.11, openSUSE Linux 15

Microsoft Windows Operating Systems Supported

Windows 7, Windows 7 x64, Windows 8, Windows 8 x64. Windows 8.1. Windows 8.1 x64, Windows 10, Windows 11

Novell Operating Systems Supported

Novell NetWare 6.5 Open Enterprise Server, Novell Open Enterprise Server 2 on SUSE Linux Enterprise Server 10 SP4, Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64), Novell Open Enterprise Server 11 (SP3) on SuSE Linux Enterprise Server 12 SP1 (x86 and x64), Novell Open Enterprise Server 15 (SP1) on SuSE Linux Enterprise Server 11 SP4 (x86 and x64)

Included Paper Handling

250-Sheet Input, Integrated Duplex, Single-Sheet Manual Feed, 100-Sheet Output Bin

Optional Paper Handling

250-Sheet Tray

Paper Input Capacity, Standard

Up to 250+1 pages 75 gsm bond

Paper Input Capacity, Maximum Up to 750+1 pages 75 gsm bond

Paper Output Capacity, Standard

Up to 100 pages 75 gsm bond

Paper Output Capacity, Maximum

Up to 100 pages 75 gsm bond Paper Weight Range Supported - Standard

Tray (gsm)

60 - 162 asm ADF

50-Sheet Automatic Document Feeder

ADF Paper Input Capacity

Up to 50 pages 75 gsm bond

ADF Paper Output Capacity

Up to 50 pages 75 gsm bond **Finishing Option**

Number of Paper Inputs, Standard

Number of Paper Inputs, Maximum

Media Types Supported

Card Stock, Envelopes, Glossy paper, Paper Labels, Plain Paper, Hagaki Card, Refer to the Paper & Specialty Media Guide

Media Sizes Supported

10 Envelope, 7 3/4 Envelope, 9 Envelope, A4, A5, B5 Envelope, C5 Envelope, DL Envelope, Hagaki Card, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

Standard Connectivity

USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front Hi-Speed USB port Compatible with USB 2.0 Specification (Type A), 802.11ac Wireless

Direct USB

Ethernet Network

Wireless

Yes



Network Protocol Support

TCP/IP IPv4, TCP/IP IPv6, TCP, UDP

Network Printing Methods

Enhanced IP (Port 9400), FTP, TFTP, IPP 1.0, 1.1, 2.0 (Internet Printing Protocol), Microsoft Web Services WSD

Network Management Protocols¹

HTTP, HTTPs (SSL/TLS), SNMPv1, SNMPv2c, SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, DDNS, mDNS, ARP, NTP, Finger,

Network Security

SNMPv3, TCP/IP port access control, 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS, IPSec

Printable Area (metric)

4.2 mm of the top, bottom, right and left edges (within)

Printer Languages (Standard)

PCL 5c Emulation, PCL 5e Emulation, PCL 6 Emulation, PostScript 3 Emulation, Direct Image, PDF 1.7 emulation, PCLm

Fonts and Symbol Sets

3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts, OCR-A, OCR-B scalable PCL 5e fonts, For more information, refer to the Technical Reference., 91 scalable PostScript fonts, 89 scalable PCL fonts

Laser Cartridge Yields (up to)

1,500-page Black and Colour (CMYK)
Cartridges, 6,000-page Black Extra High Yield
Cartridge, Average continuous cartridge yield
is stated number of standard pages as listed.
Declared yield value in accordance with ISO/
IEC 19798., 6,700-page Colour (CMY) Extra
High Yield Cartridges

Cartridge(s) Shipping with Product

1,500-page Colour (CMY) Return Programme Toner Cartridges, 1,500-page Black Return Programme Toner Cartridge

Replacement Cartridges:

Product functions only with replacement cartridges designed for use in a specific geographical region. See www.lexmark.com/regions for more details.

Packaged Size (mm - H x W x D)

519 x 440 x 556 mm

Packaged Weight, kg

22.7 kg

Size (mm - $H \times W \times D$)

344.4 x 411.2 x 394.1 mm

Weight

19.4 kg

Noise level (Idle mode)

14 dBA

Noise Level (Print), Operating

51/52 dBA

Duplex Print Noise Level, Operating

50/52 dBA

Noise Level (Copy), Operating dBA

Noise Level (Scan), Operating

dBA

Quiet Mode

45 dBA

ENERGY STAR

Average Power (Hibernate Mode)

watts

Average Power (Sleep Mode)

1.3 watts

Average Power (Ready Mode)

17.5 watts

Average Power (Printing)

400 watts

Average Power while Printing Duplex

275 watts

Average Power (Copying)

395 watts

Average Power (Scanning)

21 watts

ENERGY STAR Typical Electricity

Consumption (TEC)

0.37 kilowatt-hours per week

Product Guarantee

1-Year Onsite Service

Product Certifications

ENERGY STAR, ICES-003 Class B, BSMI Class B, US FDA, UL 60950-1, FCC Class B, cUL CAN/CSA-C22.2 60950-1, CB EN/IEC 60950-1, CB EN/IEC 60950-1, CE EN/IEC 60825-1, CE DoC (EN 62301 Class B, EN 62311, CE EN/IEC 60950-1, CE EN/IEC 60825-1, EN 61000-3, EN 55022 Class B, EN 55024, UL), EFTA (CE), KCC, CCC, CECP, CEL, C-tick DoC, UL-AR, KC mark, UL GS mark, UCRF, EC 1275, DE-UZ 219, CNS-13438/14336, Wi-Fi CERTIFIED, China Green Product (CGP), Mopria Certified

Maximum Monthly Duty Cycle

Up to 75000 pages per month³

Recommended Monthly Page Volume

750 - 5000 pages²

Specified Operating Environment

Humidity: 8 to 80% Relative Humidity, Altitude: 0 - 3048 Metres (10,000 Feet), Temperature: 10 to 32°C (50 to 90°F)

License/Agreement Terms

Printers are sold subject to certain license/ agreement conditions. See www.lexmark.com/ printerlicense for details.

Country of Origin

China (PRC)

UNSPSC Code

43212110




¹This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)

^{2&}quot;Recommended Monthly Page Volume" is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage.

^{3&}quot;Maximum Monthly Duty Cycle" is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs.

⁴Print and copy speeds measured in accordance with ISO/ IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.



Callout	Availability	Description
1	Standard	7.2 cm (2.8-inch) LCD touch panel
2	Standard	250-Sheet Tray
3	Optional	Optional 250 Sheet tray
4	Optional	

P/N	Toner Cartridges
20N0W00	Lexmark CS/CX331, 431, C/MC3224,
	3326, 3426 15K Waste Container
20N20C0	Lexmark CS/CX331, 431 Cyan Return
	Programme 1.5K Print Cartridge
20N20M0	Lexmark CS/CX331, 431 Magenta
	Return Programme 1.5K Print
	Cartridge
20N20Y0	Lexmark CS/CX331, 431 Yellow
	Return Programme 1.5K Print
	Cartridge
20N20K0	Lexmark CS/CX331, 431 Black Return
	Programme 1.5K Print Cartridge
20N2XC0	Lexmark CS/CX431 Cyan Return
	Programme 6.7K Print Cartridge
20N2XM0	Lexmark CS/CX431 Magenta Return
	Programme 6.7K Print Cartridge
20N2XY0	Lexmark CS/CX431 Yellow Return
	Programme 6.7K Print Cartridge
20N2XK0	Lexmark CS/CX431 Black Return
	Programme 6K Print Cartridge
20N0X20	Lexmark CS/CX431 Cyan 6.7K Print
	Cartridge
20N0X30	Lexmark CS/CX431 Magenta 6.7K
	Print Cartridge
20N0X40	Lexmark CS/CX431 Yellow 6.7K Print
	Cartridge
20N0X10	Lexmark CS/CX431 Black 6K Print
	Cartridge
P/N	Paper Handling
40N4250	250-Sheet Tray
P/N	Furniture
40C2300	Adjustable Stand
P/N	Connectivity
1021294	USB (2 Meter) Cable

